



G2R-1B-E DC24 Information

Heisener.com

Part Number G2R-1B-E DC24

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 16A 24V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G2R-1B-E DC24 Specifications

Manufacturer G2R-1B-E DC24 Manufacturer Omron Electronics Inc-EMC Div Category Relays Power Relays, Over 2 Amps Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 21.6mA Coil Voltage 24VDC Contact Form SPST-NC (1 Form B) Contact Rating (Current) 16A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current21.6mACoil Voltage24VDCContact FormSPST-NC (1 Form B)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)3.6 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G2R-1B-E DC24
Package Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 21.6mA Coil Voltage 24VDC Contact Form SPST-NC (1 Form B) Contact Rating (Current) 16A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Trrmination Style PCP in	Manufacturer	Omron Electronics Inc-EMC Div
Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 21.6mA Coil Voltage 24VDC Contact Form SPST-NC (1 Form B) Contact Rating (Current) 16A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Category	Relays
SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current21.6mACoil Voltage24VDCContact FormSPST-NC (1 Form B)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)3.6 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 21.6mA Coil Voltage 24VDC Contact Form SPST-NC (1 Form B) Contact Rating (Current) 16A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil TypeNon LatchingCoil Current21.6mACoil Voltage24VDCContact FormSPST-NC (1 Form B)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)3.6 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Series	G2R
Coil Current Coil Voltage 24VDC Contact Form SPST-NC (1 Form B) Contact Rating (Current) 16A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form SPST-NC (1 Form B) Contact Rating (Current) 16A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 5ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPST-NC (1 Form B) Contact Rating (Current) 16A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 5ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style	Coil Current	21.6mA
Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style	Coil Voltage	24VDC
Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPST-NC (1 Form B)
Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	16A
Turn Off Voltage (Min) Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	380VAC, 125VDC - Max
Operate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	16.8 VDC
Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	3.6 VDC
Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Operate Time	15ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	Sealed - Flux Protection
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
Topoli Milato		Report errors?

G2R-1B-E DC24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G2R-1B-E DC24 Payment Methods





















G2R-1B-E DC24 Shipping Methods













If you have any question about G2R-1B-E DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com