

### **G2R-2-AC110 Information**



For Reference Only

Part Number G2R-2-AC110

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE DPDT 5A 110V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **G2R-2-AC110 Specifications**

Manufacturer Part Number  Manufacturer  Omron Electronics Inc-EMC Div  Relays  Power Relays, Over 2 Amps  - Series  G2R  Relay Type  General Purpose  Coil Type  Non Latching  Coil Current  10.6mA  Coil Voltage  110VAC  Contact Form  DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  380VAC, 125VDC - Max  Turn Off Voltage (Min)  Operate Time  Release Time  10ms  Features  Sealed - Flux Protection  Mounting Type  Termination Style  Report errors?		
Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         G2R           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         10.6mA           Coil Voltage         110VAC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         5A           Switching Voltage         380VAC, 125VDC - Max           Turn On Voltage (Max)         88 VAC           Turn Off Voltage (Min)         33 VAC           Operate Time         15ms           Release Time         10ms           Features         Sealed - Flux Protection           Mounting Type         Through Hole           Termination Style         PC Pin	Manufacturer Part Number	G2R-2-AC110
Power Relays, Over 2 Amps	Manufacturer	Omron Electronics Inc-EMC Div
Package         -           Series         G2R           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         10.6mA           Coil Voltage         110VAC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         5A           Switching Voltage         380VAC, 125VDC - Max           Turn On Voltage (Max)         88 VAC           Turn Off Voltage (Min)         33 VAC           Operate Time         15ms           Release Time         10ms           Features         Sealed - Flux Protection           Mounting Type         Through Hole           Termination Style         PC Pin	Category	Relays
Series         G2R           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         10.6mA           Coil Voltage         110VAC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         5A           Switching Voltage         380VAC, 125VDC - Max           Turn On Voltage (Max)         88 VAC           Turn Off Voltage (Min)         33 VAC           Operate Time         15ms           Release Time         10ms           Features         Sealed - Flux Protection           Mounting Type         Through Hole           Termination Style         PC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose  Non Latching  Coil Type Non Latching  10.6mA  Coil Voltage 110VAC Contact Form DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage 380VAC, 125VDC - Max  Turn On Voltage (Max)  Turn Off Voltage (Min) 33 VAC Operate Time 15ms  Release Time 10ms  Features Sealed - Flux Protection  Mounting Type Through Hole  Termination Style	Package	-
Coil Type Coil Current 10.6mA  Coil Voltage 110VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style	Series	G2R
Coil Current Coil Voltage 110VAC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style	Relay Type	General Purpose
Coil Voltage 110VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current) 5A  Switching Voltage 380VAC, 125VDC - Max  Turn On Voltage (Max) 88 VAC  Turn Off Voltage (Min) 33 VAC  Operate Time 15ms  Release Time 10ms  Features Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Coil Current	10.6mA
Contact Rating (Current)  Switching Voltage  380VAC, 125VDC - Max  Turn On Voltage (Max)  88 VAC  Turn Off Voltage (Min)  33 VAC  Operate Time  15ms  Release Time  10ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style	Coil Voltage	110VAC
Switching Voltage 380VAC, 125VDC - Max  Turn On Voltage (Max) 88 VAC  Turn Off Voltage (Min) 33 VAC  Operate Time 15ms  Release Time 10ms  Features Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  15ms  Release Time  10ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  88 VAC  15ms  Sealed - Flux Protection  PC Pin	Contact Rating (Current)	5A
Turn Off Voltage (Min)  Operate Time  15ms  Release Time  10ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Switching Voltage	380VAC, 125VDC - Max
Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	88 VAC
Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	33 VAC
Features Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Operate Time	15ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	10ms
Termination Style PC Pin	Features	Sealed - Flux Protection
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

#### **G2R-2-AC110 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **G2R-2-AC110 Payment Methods**



















### **G2R-2-AC110** Shipping Methods













If you have any question about G2R-2-AC110, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com