

G2R-2-AC220

G2R-2-AC220 Information

	Part Number	G2R-2-AC220
	Manufacturer	Omron Electronics Inc-EMC Div
	Category	Relays Power Relays, Over 2 Amps
	Description	RELAY GEN PURPOSE DPDT 5A 220V
	Package	-
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



G2R-2-AC220 Specifications

Manufacturer Part Number G2R-2AC220 Manufacturer Omron Electronics Inc-EMC Div Category Relays Category Power Relays, Over 2 Amps Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 4.1mA Coil Current 20VAC Cotact Form DPDT (2 Form C) Cotact Rating (Current) SA Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 176 VAC Querta Time Sans Release Time Ioms Fatures Sael - Flux Protection Mouning Type Protege Hole		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current4.1mACoil Otage200 ACContact FormDPDT (2 Form C)Contact Rating (Current)SASwitching Yoltage380VAC, 125VDC - MaxTurn On Voltage (Max)166 VACCurrentSinsRelease TimeJomsFeaturesSealed - Flux ProtectionMouting TypeFlux ProtectionFernination StylePC Pin	Manufacturer Part Number	G2R-2-AC220
PackagePower Relays, Over 2 AmpsPackage-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current4.1mACoil Voltage220VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)176 VACOperate Time5.5msRelease Time10msFeaturesScaled - Flux ProtectionMounting TypeThrough HoleFermination Style9C Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current4.1mACoil Voltage20VACContact FormDPDT (2 Form C)Contact Rating (Current)SASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)176 VACOperate Time66 VACRelease TimeIomsFeaturesSael - Flux ProtectionMounting TypePC Pin	Category	Relays
SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current4.1mACoil Voltage20VACContact FormDPDT (2 Form C)Contact Rating (Current)SASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)176 VACOperate Time15msRelease TimeIomsFeaturesSaled - Flux ProtectionMounting TypePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current4.1mACoil Voltage220VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)176 VACOperate Time15msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypePC Pin	Package	-
Coil TypeNon LachingCoil Current4.1mACoil Voltage20VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)176 VACCurrent Form66 VACPreate Time15msRelease Time10msFeaturesSaled - Flux ProtectionMounting TypeFinogh HolePrinniation StylePC Pin	Series	G2R
Coil Current4.1mACoil Voltage20VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)176 VACCurrent friege (Min)66 VACOperate Time15msRelease Time10msFeaturesSaled - Flux ProtectionMounting TypeFor MarkPremination StylePC Pin	Relay Type	General Purpose
Coil Voltage220VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)176 VACTurn Off Voltage (Min)66 VACOperate Time15msRelease Time10msFeaturesSaled - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Coil Type	Non Latching
Note of generationDPDT (2 Form C)Contact Form5ASwitching (Current)380VAC, 125VDC - MaxSwitching Voltage (Max)176 VACTurn On Voltage (Max)66 VACOperate Time15msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination Style9C Pin	Coil Current	4.1mA
Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)176 VACTurn Off Voltage (Min)66 VACOperate Time15msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Coil Voltage	220VAC
Switching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)176 VACTurn Off Voltage (Min)66 VACOperate Time15msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)176 VACTurn Off Voltage (Min)66 VACOperate Time15msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Contact Rating (Current)	5A
Turn Off Voltage (Min)66 VACOperate Time15msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Switching Voltage	380VAC, 125VDC - Max
Operate Time15msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	176 VAC
Release Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Turn Off Voltage (Min)	66 VAC
FeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Operate Time	15ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	10ms
Termination Style PC Pin	Features	Sealed - Flux Protection
-	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
· · · · · · · · · · · · · · · · · · ·		Report errors?

G2R-2-AC220 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

G2R-2-AC220 Payment Methods



G2R-2-AC220 Shipping Methods



If you have any question about G2R-2-AC220, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com