

## **G2R-2-AC6 Information**



For Reference Only

Part Number G2R-2-AC6

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GENERAL PURPOSE DPDT 5A 6V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **G2R-2-AC6 Specifications**

Manufacturer       G2R-2-AC6         Manufacturer       Omron Electronics Inc-EMC Div         Category       Relays         Power Relays, Over 2 Amps         Package       -         Series       G2R         Relay Type       General Purpose         Coil Type       Non Latching         Coil Current       150mA         Coil Voltage       6VAC         Contact Form       DPDT (2 Form C)         Contact Rating (Current)       5A         Switching Voltage       380VAC, 125VDC - Max         Turn On Voltage (Max)       4.8 VAC         Turn Off Voltage (Min)       1.8 VAC         Operate Time       15ms         Release Time       10ms         Features       Sealed - Flux Protection         Mounting Type       Through Hole         Termination Style       PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current150mACoil Voltage6VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)4.8 VACTurn Off Voltage (Min)1.8 VACOperate Time15msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G2R-2-AC6
Package-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current150mACoil Voltage6VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)4.8 VACTurn Off Voltage (Min)1.8 VACOperate Time15msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package         -           Series         G2R           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         150mA           Coil Voltage         6VAC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         5A           Switching Voltage         380VAC, 125VDC - Max           Turn On Voltage (Max)         4.8 VAC           Turn Off Voltage (Min)         1.8 VAC           Operate Time         15ms           Release Time         10ms           Features         Sealed - Flux Protection           Mounting Type         Through Hole           Termination Style         PC Pin	Category	Relays
SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current150mACoil Voltage6VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)4.8 VACTurn Off Voltage (Min)1.8 VACOperate Time15msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 150mA Coil Voltage 6VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.8 VAC Turn Off Voltage (Min) 1.8 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil TypeNon LatchingCoil Current150mACoil Voltage6VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)4.8 VACTurn Off Voltage (Min)1.8 VACOperate Time15msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Series	G2R
Coil Current Coil Voltage 6VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.8 VAC Turn Off Voltage (Min) 1.8 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style	Relay Type	General Purpose
Coil Voltage 6VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.8 VAC Turn Off Voltage (Min) 1.8 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current)  5A  Switching Voltage  380VAC, 125VDC - Max  Turn On Voltage (Max)  4.8 VAC  Turn Off Voltage (Min)  1.8 VAC  Operate Time  15ms  Release Time  10ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style	Coil Current	150mA
Contact Rating (Current)  Switching Voltage  380VAC, 125VDC - Max  Turn On Voltage (Max)  4.8 VAC  Turn Off Voltage (Min)  1.8 VAC  Operate Time  15ms  Release Time  10ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style	Coil Voltage	6VAC
Switching Voltage  380VAC, 125VDC - Max  Turn On Voltage (Max)  4.8 VAC  Turn Off Voltage (Min)  1.8 VAC  Operate Time  15ms  Release Time  10ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  4.8 VAC  Turn Off Voltage (Min)  1.8 VAC  Operate Time  15ms  Release Time  10ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  4.8 VAC  1.8 VAC	Contact Rating (Current)	5A
Turn Off Voltage (Min)  1.8 VAC  Operate Time 15ms  Release Time 10ms  Features Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Switching Voltage	380VAC, 125VDC - Max
Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	4.8 VAC
Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	1.8 VAC
Features Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Operate Time	15ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	10ms
Termination Style PC Pin	Features	Sealed - Flux Protection
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
Topoli Milato		Report errors?

#### **G2R-2-AC6** Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **G2R-2-AC6** Payment Methods



















### **G2R-2-AC6 Shipping Methods**













If you have any question about G2R-2-AC6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com