



#### **G2R-2-AUL DC12 Information**



For Reference Only

Part Number G2R-2-AUL DC12

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE DPDT 5A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### **G2R-2-AUL DC12 Specifications**

Manufacturer Part Number         G2R-2-AUL DC12           Manufacturer         Omron Electronics Inc-EMC Div           Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         G2R           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         43.6mA           Coil Voltage         12VDC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         5A           Switching Voltage         380VAC, 125VDC - Max           Turn On Voltage (Max)         8.4 VDC           Turn Off Voltage (Min)         1.8 VDC           Operate Time         15ms           Release Time         5ms           Features         Sealed - Flux Protection           Mounting Type         Through Hole           Termination Style         PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current43.6mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G2R-2-AUL DC12
Package Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 43.6mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 1.8 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 5 sms Features Sealed - Flux Protection Mounting Type Termination Style PC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package         -           Series         G2R           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         43.6mA           Coil Voltage         12VDC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         5A           Switching Voltage         380VAC, 125VDC - Max           Turn On Voltage (Max)         8.4 VDC           Turn Off Voltage (Min)         1.8 VDC           Operate Time         15ms           Release Time         5ms           Features         Sealed - Flux Protection           Mounting Type         Through Hole           Termination Style         PC Pin	Category	Relays
Series         G2R           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         43.6mA           Coil Voltage         12VDC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         5A           Switching Voltage         380VAC, 125VDC - Max           Turn On Voltage (Max)         8.4 VDC           Turn Off Voltage (Min)         1.8 VDC           Operate Time         15ms           Release Time         5ms           Features         Sealed - Flux Protection           Mounting Type         Through Hole           Termination Style         PC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current43.6mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current43.6mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Series	G2R
Coil Current 43.6mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 5ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  380VAC, 125VDC - Max  Turn On Voltage (Max)  8.4 VDC  Turn Off Voltage (Min)  1.8 VDC  Operate Time  15ms  Release Time  5ms  Release Time  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style	Coil Current	43.6mA
Contact Rating (Current)  Switching Voltage  380VAC, 125VDC - Max  Turn On Voltage (Max)  8.4 VDC  Turn Off Voltage (Min)  1.8 VDC  Operate Time  15ms  Release Time  5ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Coil Voltage	12VDC
Switching Voltage  380VAC, 125VDC - Max  Turn On Voltage (Max)  8.4 VDC  Turn Off Voltage (Min)  1.8 VDC  Operate Time  15ms  Release Time  5ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  1.8 VDC  Operate Time  15ms  Release Time  5ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Contact Rating (Current)	5A
Turn Off Voltage (Min)  Operate Time  15ms  Release Time  5ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Switching Voltage	380VAC, 125VDC - Max
Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	8.4 VDC
Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	1.8 VDC
Features Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Operate Time	15ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	Sealed - Flux Protection
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

#### **G2R-2-AUL DC12 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **G2R-2-AUL DC12 Payment Methods**





















### **G2R-2-AUL DC12 Shipping Methods**













If you have any question about G2R-2-AUL DC12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com