

G2R-2-DC110 Information



For Reference Only

Part Number G2R-2-DC110

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 5A 110V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G2R-2-DC110 Specifications

Manufacturer Part Number G2R-2-DC110 Manufacturer Omron Electronics Inc-EMC Div Category Relays Power Relays, Over 2 Amps Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 4.8mA Coil Voltage 110VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 77 VDC
Category Relays Power Relays, Over 2 Amps Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 4.8mA Coil Voltage 110VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max
Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 4.8mA Coil Voltage 110VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max
Package - G2R Relay Type General Purpose Coil Type Non Latching Coil Current 4.8mA Coil Voltage 110VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max
Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 4.8mA Coil Voltage 110VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max
Relay Type General Purpose Coil Type Non Latching Coil Current 4.8mA Coil Voltage 110VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max
Coil Type Non Latching Coil Current 4.8mA Coil Voltage 110VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max
Coil Current 4.8mA Coil Voltage 110VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max
Coil Voltage 110VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max
Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max
Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max
Switching Voltage 380VAC, 125VDC - Max
Turn On Voltage (Max) 77 VDC
Turn Off Voltage (Min) 16.5 VDC
Operate Time 15ms
Release Time 5ms
Features Sealed - Flux Protection
Mounting Type Through Hole
Termination Style PC Pin
Report errors?

G2R-2-DC110 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G2R-2-DC110 Payment Methods



















G2R-2-DC110 Shipping Methods













If you have any question about G2R-2-DC110, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com