

G2R-2 DC18 Information



For Reference Only

Part Number G2R-2 DC18

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 5A 18V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G2R-2 DC18 Specifications

Manufacturer Part Number G2R-2 DC18 Manufacturer Omron Electronics Inc-EMC Div Category Relays Power Relays, Over 2 Amps Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 29.4mA Coil Voltage 18VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 12.6 VDC Turn Off Voltage (Min) 2.7 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin		
CategoryRelays Power Relays, Over 2 AmpsPackage-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current29.4mACoil Voltage18VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)12.6 VDCTurn Off Voltage (Min)2.7 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough Hole	Manufacturer Part Number	G2R-2 DC18
Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 29.4mA Coil Voltage 18VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 12.6 VDC Turn Off Voltage (Min) 2.7 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Trup One Series Series Series Series Series Series Series Through Hole	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current29.4mACoil Voltage18VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)12.6 VDCTurn Off Voltage (Min)2.7 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough Hole	Category	Relays
SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current29.4mACoil Voltage18VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)12.6 VDCTurn Off Voltage (Min)2.7 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough Hole		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 29.4mA Coil Voltage 18VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 12.6 VDC Turn Off Voltage (Min) 2.7 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole	Package	-
Coil Type Non Latching Coil Current 29.4mA Coil Voltage 18VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 12.6 VDC Turn Off Voltage (Min) 2.7 VDC Operate Time 15ms Release Time 5ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole	Series	G2R
Coil Current 29.4mA Coil Voltage 18VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 12.6 VDC Turn Off Voltage (Min) 2.7 VDC Operate Time 15ms Release Time 5ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole	Relay Type	General Purpose
Coil Voltage 18VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 12.6 VDC Turn Off Voltage (Min) 2.7 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 12.6 VDC Turn Off Voltage (Min) 2.7 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole	Coil Current	29.4mA
Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 12.6 VDC Turn Off Voltage (Min) 2.7 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole	Coil Voltage	18VDC
Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 12.6 VDC Turn Off Voltage (Min) 2.7 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 12.6 VDC Turn Off Voltage (Min) 2.7 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole	Switching Voltage	380VAC, 125VDC - Max
Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole	Turn On Voltage (Max)	12.6 VDC
Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole	Turn Off Voltage (Min)	2.7 VDC
Features Sealed - Flux Protection Mounting Type Through Hole	Operate Time	15ms
Mounting Type Through Hole	Release Time	5ms
	Features	Sealed - Flux Protection
Termination Style PC Pin	Mounting Type	Through Hole
	Termination Style	PC Pin
Report errors?		Report errors?

G2R-2 DC18 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G2R-2 DC18 Payment Methods



















G2R-2 DC18 Shipping Methods













If you have any question about G2R-2 DC18, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com