

# G2R-2-S AC12(S)

## G2R-2-S AC12(S) Information



Number	G2R-2-S AC12(S)	
ufacturer	Omron Automation and Safety	
gory	Relays Power Relays, Over 2 Amps	
ription	RELAY GEN PURPOSE DPDT 5A 12V	
age	-	
	For the pricing/inventory/lead time, please contac	
	us	
	Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## G2R-2-S AC12(S) Specifications

Manufacturer Part NumberG2R-2-S AC12(S)ManufacturerOmron Automation and SafetyCategoryRelaysPackage-SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil CurrentSinsaContact FormPDPT (2 Form C)Contact Rating (Current)SinOVAC PAMASSwitching VoltageSinOVAC PAMASTurn On Voltage (Max)SinOVAC PAMASPoperate TimeSinSColtartsSinSRelayer TimeSinSPoperatimeSinSRelayer TimeSinSRelayer TimeSinSPoperatimeSinSFatures </th <th></th> <th></th>		
CategoryRelaysPackage-SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VACTurn Off Voltage (Min)3.6 VACParter Time15msRelease Time-Mounting TypeSocketable	Manufacturer Part Number	G2R-2-S AC12(S)
PackagePower Relays, Over 2 AmpsPackage-SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VACTurn Off Voltage (Min)3.6 VACOperate Time15msRelease Time-Features-Mounting TypeSocketable	Manufacturer	Omron Automation and Safety
Package-SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VACContact FormDPDT (2 Form C)Contact Rating (Current)SASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VACTurn Off Voltage (Min)3.6 VACOperate Time15msRelease Time-Hounting TypeSocketable	Category	Relays
SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VACTurn Off Voltage (Min)3.6 VACOperate Time15msRelease Time5Features-Mounting TypeSocketable		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current75mACoil Voltage12VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VACOperate Time15msRelease Time15msFeatures-Mounting TypeSocketable	Package	-
Coil TypeNon LatchingCoil Current75mACoil Voltage12VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VACTurn Off Voltage (Min)3.6 VACOperate Time15msRelease Time15msFeatures-Mounting TypeSocketable	Series	G2RS
Coil Current75mACoil Voltage12VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VACTurn Off Voltage (Min)3.6 VACOperate Time15msRelease Time15msFeatures-Mounting TypeSocketable	Relay Type	General Purpose
Coil Voltage12VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VACTurn Off Voltage (Min)3.6 VACOperate Time15msRelease Time-Features-Mounting TypeSocketable	Coil Type	Non Latching
Contact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VACTurn Off Voltage (Min)3.6 VACOperate Time15msRelease Time-Features-Mounting TypeSocketable	Coil Current	75mA
Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VACTurn Off Voltage (Min)3.6 VACOperate Time15msRelease Time15msFeatures-Mounting TypeSocketable	Coil Voltage	12VAC
Switching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VACTurn Off Voltage (Min)3.6 VACOperate Time15msRelease Time15msFeatures-Mounting TypeSocketable	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)9.6 VACTurn Off Voltage (Min)3.6 VACOperate Time15msRelease Time15msFeatures-Mounting TypeSocketable	Contact Rating (Current)	5A
Turn Off Voltage (Min)3.6 VACOperate Time15msRelease Time15msFeatures-Mounting TypeSocketable	Switching Voltage	380VAC, 125VDC - Max
Operate Time15msRelease Time15msFeatures-Mounting TypeSocketable	Turn On Voltage (Max)	9.6 VAC
Release Time15msFeatures-Mounting TypeSocketable	Turn Off Voltage (Min)	3.6 VAC
Features-Mounting TypeSocketable	Operate Time	15ms
Mounting Type Socketable	Release Time	15ms
	Features	-
Termination Style Plug In	Mounting Type	Socketable
	Termination Style	Plug In
Report errors		Report errors?

### G2R-2-S AC12(S) Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### G2R-2-S AC12(S) Payment Methods



## G2R-2-S AC12(S) Shipping Methods



If you have any question about G2R-2-S AC12(S), please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com