

G2R-2-S AC120(S) Information



For Reference Only

Part Number G2R-2-S AC120(S)

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 5A 120V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G2R-2-S AC120(S) Specifications

Manufacturer Part Number G2R-2-S AC120(S) Manufacturer Omron Automation and Safety Category Relays Power Relays, Over 2 Amps Package - Series G2RS Relay Type General Purpose Coil Type Non Latching Coil Current 7.5mA Coil Voltage 120VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) 36 VAC Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable Termination Style Plug In		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current7.5mACoil Voltage120VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)96 VACTurn Off Voltage (Min)36 VACOperate Time15msRelease Time15msFeatures-Mounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	G2R-2-S AC120(S)
Package - Series G2RS Relay Type General Purpose Coil Type Non Latching Coil Current 7.5mA Coil Voltage 120VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) 36 VAC Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable Termination Style Plug In	Manufacturer	Omron Automation and Safety
Package - Series G2RS Relay Type General Purpose Coil Type Non Latching Coil Current 7.5mA Coil Voltage 120VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) 36 VAC Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable Termination Style Plug In	Category	Relays
SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current7.5mACoil Voltage120VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)96 VACTurn Off Voltage (Min)36 VACOperate Time15msRelease Time15msFeatures-Mounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 7.5mA Coil Voltage 120VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) 36 VAC Operate Time 15ms Release Time 15ms Release Time 15ms Features - Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current7.5mACoil Voltage120VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)96 VACTurn Off Voltage (Min)36 VACOperate Time15msRelease Time15msFeatures-Mounting TypeSocketableTermination StylePlug In	Series	G2RS
Coil Current7.5mACoil Voltage120VACContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)96 VACTurn Off Voltage (Min)36 VACOperate Time15msRelease Time15msFeatures-Mounting TypeSocketableTermination StylePlug In	Relay Type	General Purpose
Coil Voltage 120VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) 36 VAC Operate Time 15ms Release Time 15ms Features Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 7urn Off Voltage (Min) Operate Time 15ms Release Time 15ms Release Time 15ms Features - Mounting Type Socketable Termination Style	Coil Current	7.5mA
Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) 36 VAC Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable Termination Style Plug In	Coil Voltage	120VAC
Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) 36 VAC Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable Termination Style Plug In	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 7 Turn Off Voltage (Min) 96 VAC Turn Off Voltage (Min) 36 VAC Operate Time 15 ms Release Time 15 ms Features - Mounting Type Socketable Termination Style Plug In	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable Termination Style Plug In	Switching Voltage	380VAC, 125VDC - Max
Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	96 VAC
Release Time 15ms Features - Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	36 VAC
Features - Mounting Type Socketable Termination Style Plug In	Operate Time	15ms
Mounting Type Socketable Termination Style Plug In	Release Time	15ms
Termination Style Plug In	Features	-
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

G2R-2-S AC120(S) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G2R-2-S AC120(S) Payment Methods





















G2R-2-S AC120(S) Shipping Methods













If you have any question about G2R-2-S AC120(S), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com