

G2R-2-S DC24(S) Information



For Reference Only

Part Number G2R-2-S DC24(S)

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 5A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G2R-2-S DC24(S) Specifications

Manufacturer Part Number G2R-2-S DC24(S) Manufacturer Omron Automation and Safety Category Relays Power Relays, Over 2 Amps Package - Series G2RS Relay Type General Purpose Coil Type Non Latching Coil Current 21.6mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 10ms Features - Mounting Type Socketable		
Category Relays Power Relays, Over 2 Amps Package - Series G2RS Relay Type General Purpose Coil Type Non Latching Coil Current 21.6mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 10ms Features - Mounting Type Socketable	Manufacturer Part Number	G2R-2-S DC24(S)
Package - Series G2RS Relay Type General Purpose Coil Type Non Latching Coil Current 21.6mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 10ms Features - Mounting Type Socketable	Manufacturer	Omron Automation and Safety
Package-SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current21.6mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)3.6 VDCOperate Time15msRelease Time10msFeatures-Mounting TypeSocketable	Category	Relays
Series G2RS Relay Type General Purpose Coil Type Non Latching Coil Current 21.6mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 10ms Features - Mounting Type Socketable		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 21.6mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 10ms Features - Mounting Type Socketable	Package	-
Coil TypeNon LatchingCoil Current21.6mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)3.6 VDCOperate Time15msRelease Time10msFeatures-Mounting TypeSocketable	Series	G2RS
Coil Current Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 10ms Features Mounting Type Socketable	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 10ms Features - Mounting Type Socketable	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 10ms Features - Mounting Type Socketable	Coil Current	21.6mA
Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 10ms Features - Mounting Type Socketable	Coil Voltage	24VDC
Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 10ms Features - Mounting Type Socketable	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 15ms Release Time 10ms Features - Mounting Type Socketable	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time 15ms Release Time 10ms Features - Mounting Type Socketable	Switching Voltage	380VAC, 125VDC - Max
Operate Time 15ms Release Time 10ms Features - Mounting Type Socketable	Turn On Voltage (Max)	16.8 VDC
Release Time 10ms Features - Mounting Type Socketable	Turn Off Voltage (Min)	3.6 VDC
Features - Mounting Type Socketable	Operate Time	15ms
Mounting Type Socketable	Release Time	10ms
	Features	-
m ' ' ' ' ' C ' 1	Mounting Type	Socketable
remination Style Plug In	Termination Style	Plug In
Report errors?		Report errors?

G2R-2-S DC24(S) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G2R-2-S DC24(S) Payment Methods



















G2R-2-S DC24(S) Shipping Methods













If you have any question about G2R-2-S DC24(S), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com