

G2R-2-SN DC48(S) Information



For Reference Only

Part Number G2R-2-SN DC48(S)

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 5A 48V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G2R-2-SN DC48(S) Specifications

Manufacturer Part Number G2R-2-SN DC48(S) Manufacturer Omron Automation and Safety Category Relays Package - Series G2RS Relay Type General Purpose Coil Type Non Latching Coil Current 11.4mA Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 15ms Release Time 10ms Features LED Indicator Mounting Type Socketable Termination Style Plug In		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current11.4mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)7.2 VDCOperate Time15msRelease Time10msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	G2R-2-SN DC48(S)
Package-SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current11.4mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)7.2 VDCOperate Time15msRelease Time10msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Manufacturer	Omron Automation and Safety
Package - Series G2RS Relay Type General Purpose Coil Type Non Latching Coil Current 11.4mA Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 15ms Release Time 10ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Category	Relays
SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current11.4mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)7.2 VDCOperate Time15msRelease Time10msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 11.4mA Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 15ms Release Time 10ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current11.4mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)7.2 VDCOperate Time15msRelease Time10msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Series	G2RS
Coil Current Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 15ms Release Time 10ms Features LED Indicator Mounting Type Socketable Termination Style	Relay Type	General Purpose
Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 15ms Release Time 10ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 15ms Release Time 10ms Features LED Indicator Mounting Type Socketable Termination Style	Coil Current	11.4mA
Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 15ms Release Time 10ms Features LED Indicator Mounting Type Socketable Termination Style	Coil Voltage	48VDC
Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 15ms Release Time 10ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 15ms Release Time 10ms Features LED Indicator Mounting Type Socketable Termination Style 33.6 VDC 7.2 VDC 15ms LED Indicator Plug In	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time 15ms Release Time 10ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Switching Voltage	380VAC, 125VDC - Max
Operate Time 15ms Release Time 10ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	33.6 VDC
Release Time 10ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	7.2 VDC
Features LED Indicator Mounting Type Socketable Termination Style Plug In	Operate Time	15ms
Mounting Type Socketable Termination Style Plug In	Release Time	10ms
Termination Style Plug In	Features	LED Indicator
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

G2R-2-SN DC48(S) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G2R-2-SN DC48(S) Payment Methods



















G2R-2-SN DC48(S) Shipping Methods













If you have any question about G2R-2-SN DC48(S), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com