

### G2R-2-SN DC48(S) Information



For Reference Only

Part Number G2R-2-SN DC48(S)

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE DPDT 5A 48V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **G2R-2-SN DC48(S) Specifications**

Manufacturer Part Number         G2R-2-SN DC48(S)           Manufacturer         Omron Automation and Safety           Category         Relays           Package         -           Series         G2RS           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         11.4mA           Coil Voltage         48VDC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         5A           Switching Voltage         380VAC, 125VDC - Max           Turn On Voltage (Max)         33.6 VDC           Turn Off Voltage (Min)         7.2 VDC           Operate Time         15ms           Release Time         10ms           Features         LED Indicator           Mounting Type         Socketable           Termination Style         Plug In		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current11.4mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)7.2 VDCOperate Time15msRelease Time10msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	G2R-2-SN DC48(S)
Package-SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current11.4mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)7.2 VDCOperate Time15msRelease Time10msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Manufacturer	Omron Automation and Safety
Package         -           Series         G2RS           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         11.4mA           Coil Voltage         48VDC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         5A           Switching Voltage         380VAC, 125VDC - Max           Turn On Voltage (Max)         33.6 VDC           Turn Off Voltage (Min)         7.2 VDC           Operate Time         15ms           Release Time         10ms           Features         LED Indicator           Mounting Type         Socketable           Termination Style         Plug In	Category	Relays
SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current11.4mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)7.2 VDCOperate Time15msRelease Time10msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 11.4mA Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 15ms Release Time 10ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current11.4mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)7.2 VDCOperate Time15msRelease Time10msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Series	G2RS
Coil Current Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 15ms Release Time 10ms Features LED Indicator Mounting Type Socketable Termination Style	Relay Type	General Purpose
Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 15ms Release Time 10ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  380VAC, 125VDC - Max  Turn On Voltage (Max)  33.6 VDC  Turn Off Voltage (Min)  7.2 VDC  Operate Time  15ms  Release Time  10ms  Features  LED Indicator  Mounting Type  Socketable  Termination Style	Coil Current	11.4mA
Contact Rating (Current)  Switching Voltage  380VAC, 125VDC - Max  Turn On Voltage (Max)  33.6 VDC  Turn Off Voltage (Min)  7.2 VDC  Operate Time  15ms  Release Time  10ms  Features  LED Indicator  Mounting Type  Socketable  Termination Style	Coil Voltage	48VDC
Switching Voltage 380VAC, 125VDC - Max  Turn On Voltage (Max) 33.6 VDC  Turn Off Voltage (Min) 7.2 VDC  Operate Time 15ms  Release Time 10ms  Features LED Indicator  Mounting Type Socketable  Termination Style Plug In	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  15ms  Release Time  10ms  Features  LED Indicator  Mounting Type  Socketable  Termination Style  33.6 VDC  7.2 VDC  15ms  LED Indicator  Plug In	Contact Rating (Current)	5A
Turn Off Voltage (Min)  Operate Time  15ms  Release Time  10ms  Features  LED Indicator  Mounting Type  Socketable  Termination Style  Plug In	Switching Voltage	380VAC, 125VDC - Max
Operate Time 15ms Release Time 10ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	33.6 VDC
Release Time 10ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	7.2 VDC
Features LED Indicator  Mounting Type Socketable  Termination Style Plug In	Operate Time	15ms
Mounting Type Socketable Termination Style Plug In	Release Time	10ms
Termination Style Plug In	Features	LED Indicator
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

## G2R-2-SN DC48(S) Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### G2R-2-SN DC48(S) Payment Methods



















## G2R-2-SN DC48(S) Shipping Methods













If you have any question about G2R-2-SN DC48(S), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com