



## G2R-2-SND DC24(S) Information



For Reference Only

Part Number G2R-2-SND DC24(S)

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE DPDT 5A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **G2R-2-SND DC24(S) Specifications**

Manufacturer Part Number       G2R-2-SND DC24(S)         Manufacturer       Omron Automation and Safety         Category       Relays         Power Relays, Over 2 Amps         Package       -         Series       G2RS         Relay Type       General Purpose         Coil Type       Non Latching         Coil Current       21.6mA         Coil Voltage       24VDC         Contact Form       DPDT (2 Form C)         Contact Rating (Current)       5A         Switching Voltage       380VAC, 125VDC - Max         Turn On Voltage (Max)       16.8 VDC         Turn Off Voltage (Min)       3.6 VDC         Operate Time       15ms         Release Time       20ms         Features       Diode, LED Indicator         Mounting Type       Socketable         Termination Style       Plug In		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current21.6mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)3.6 VDCOperate Time15msRelease Time20msFeaturesDiode, LED IndicatorMounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	G2R-2-SND DC24(S)
Package-SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current21.6mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)3.6 VDCOperate Time15msRelease Time20msFeaturesDiode, LED IndicatorMounting TypeSocketableTermination StylePlug In	Manufacturer	Omron Automation and Safety
Package-SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current21.6mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)3.6 VDCOperate Time15msRelease Time20msFeaturesDiode, LED IndicatorMounting TypeSocketableTermination StylePlug In	Category	Relays
SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current21.6mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)3.6 VDCOperate Time15msRelease Time20msFeaturesDiode, LED IndicatorMounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 21.6mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 20ms Features Diode, LED Indicator Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current21.6mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)3.6 VDCOperate Time15msRelease Time20msFeaturesDiode, LED IndicatorMounting TypeSocketableTermination StylePlug In	Series	G2RS
Coil Current21.6mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)3.6 VDCOperate Time15msRelease Time20msFeaturesDiode, LED IndicatorMounting TypeSocketableTermination StylePlug In	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 20ms Features Diode, LED Indicator Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  380VAC, 125VDC - Max  Turn On Voltage (Max)  16.8 VDC  Turn Off Voltage (Min)  3.6 VDC  Operate Time  15ms  Release Time  20ms  Features  Diode, LED Indicator  Mounting Type  Socketable  Termination Style	Coil Current	21.6mA
Contact Rating (Current)  Switching Voltage  380VAC, 125VDC - Max  Turn On Voltage (Max)  16.8 VDC  Turn Off Voltage (Min)  3.6 VDC  Operate Time  15ms  Release Time  20ms  Features  Diode, LED Indicator  Mounting Type  Socketable  Termination Style	Coil Voltage	24VDC
Switching Voltage 380VAC, 125VDC - Max  Turn On Voltage (Max) 16.8 VDC  Turn Off Voltage (Min) 3.6 VDC  Operate Time 15ms  Release Time 20ms  Features Diode, LED Indicator  Mounting Type Socketable  Termination Style Plug In	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  16.8 VDC  Turn Off Voltage (Min)  3.6 VDC  Operate Time  15ms  Release Time  20ms  Features  Diode, LED Indicator  Mounting Type  Socketable  Termination Style  Plug In	Contact Rating (Current)	5A
Turn Off Voltage (Min)  Operate Time  15ms  Release Time  20ms  Features  Diode, LED Indicator  Mounting Type  Socketable  Termination Style  Plug In	Switching Voltage	380VAC, 125VDC - Max
Operate Time15msRelease Time20msFeaturesDiode, LED IndicatorMounting TypeSocketableTermination StylePlug In	Turn On Voltage (Max)	16.8 VDC
Release Time 20ms Features Diode, LED Indicator Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	3.6 VDC
Features Diode, LED Indicator  Mounting Type Socketable  Termination Style Plug In	Operate Time	15ms
Mounting Type Socketable Termination Style Plug In	Release Time	20ms
Termination Style Plug In	Features	Diode, LED Indicator
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
•		Report errors?

## **G2R-2-SND DC24(S) Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## G2R-2-SND DC24(S) Payment Methods



















## **G2R-2-SND DC24(S) Shipping Methods**













If you have any question about G2R-2-SND DC24(S), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com