

G2R-2-SND DC6(S)

G2R-2-SND DC6(S) Information



Part Number	G2R-2-SND DC6(S)	
Manufacturer	Omron Automation and Safety	
Category	Relays Power Relays, Over 2 Amps	
Description	RELAY GENERAL PURPOSE DPDT 5A 6V	
Package	-	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



G2R-2-SND DC6(S) Specifications

Manufacturer Part Number G2R2-2SND DC6(S) Manufacturer Omron Automation and Safety Category Relays Package Power Relays, Over 2 Amps Package - Series G2RS Relay Type General Purpose Coil Type Non Latching Coil Current S7mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) SA Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Querta Time Jons Release Time Jons Release Time Jonde, LED Indicator Mounting Type Sockatable		
CategoryRelays Power Relays, Over 2 AmpsPackage-SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current87mACoil Voltage6VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn ON Voltage (Max)4.2 VDCOperate Time5.5msRelease Time20msFeaturesDiode, LED IndicatorMounting TypeSocketableTermination StyleHug In	Manufacturer Part Number	G2R-2-SND DC6(S)
Power Relays, Over 2 AmpsPackage-SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current87mAColl Voltage6VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)4.2 VDCOperate Time0.9 VDCRelease Time20msFeaturesDiode, LED IndicatorMounting TypeSocketableTermination StyleHug In	Manufacturer	Omron Automation and Safety
Package-SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current87mAColl Voltage6VDCContact FormDPDT (2 Form C)Contact Rating (Current)SASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)4.2 VDCQperate Time0.9 VDCRelease Time20msFeaturesDiode, LED IndicatorMounting TypeSocketableTermination StyleHug In	Category	Relays
SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current87mACoil Voltage6VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.9 VDCOperate Time15msRelease Time20msFeaturesDiode, LED IndicatorMounting TypePug In		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current87mACoil Voltage6VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)0.9 VDCTurn Off Voltage (Min)0.9 VDCOperate Time20msRelease TimeDiode, LED IndicatorFeaturesSocketableMounting TypePlug In	Package	-
Coil TypeNon LatchingCoil Current87mACoil Voltage6VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.9 VDCOperate Time15msRelease Time20msFeaturesDiode, LED IndicatorMounting TypeSocketableTermination StylePlug In	Series	G2RS
Coil Current87mACoil Voltage6VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.9 VDCOperate Time15msRelease Time20msFeaturesDiode, LED IndicatorMounting TypeSocketableTermination StylePlug In	Relay Type	General Purpose
Coil Voltage6VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.9 VDCOperate Time15msRelease TimesDiode, LED IndicatorFeaturesSocketableMounting TypePug InTermination StylePug In	Coil Type	Non Latching
Contact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.9 VDCOperate Time15msRelease Time20msFeaturesDiode, LED IndicatorMounting TypeSocketableTermination StylePlug In	Coil Current	87mA
Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.9 VDCOperate Time15msRelease Time20msFeaturesDiode, LED IndicatorMounting TypeSocketableTermination StylePlug In	Coil Voltage	6VDC
Switching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.9 VDCOperate Time15msRelease Time20msFeaturesDiode, LED IndicatorMounting TypeSocketableTermination StylePlug In	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.9 VDCOperate Time15msRelease Time20msFeaturesDiode, LED IndicatorMounting TypeSocketableTermination StylePlug In	Contact Rating (Current)	5A
Turn Off Voltage (Min)0.9 VDCOperate Time15msRelease Time20msFeaturesDiode, LED IndicatorMounting TypeSocketableTermination StylePlug In	Switching Voltage	380VAC, 125VDC - Max
Operate Time15msRelease Time20msFeaturesDiode, LED IndicatorMounting TypeSocketableTermination StylePlug In	Turn On Voltage (Max)	4.2 VDC
Release Time20msFeaturesDiode, LED IndicatorMounting TypeSocketableTermination StylePlug In	Turn Off Voltage (Min)	0.9 VDC
FeaturesDiode, LED IndicatorMounting TypeSocketableTermination StylePlug In	Operate Time	15ms
Mounting TypeSocketableTermination StylePlug In	Release Time	20ms
Termination Style Plug In	Features	Diode, LED Indicator
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
•		Report errors?

G2R-2-SND DC6(S) Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE SUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

G2R-2-SND DC6(S) Payment Methods



G2R-2-SND DC6(S) Shipping Methods



If you have any question about G2R-2-SND DC6(S), please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com