



G2R-2-SNDI DC6(S) Information

Heisener.com

Part Number G2R-2-SNDI DC6(S)

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 5A 6V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G2R-2-SNDI DC6(S) Specifications

Manufacturer Part Number Manufacturer Omron Automation and Safety Relays Power Relays, Over 2 Amps Package - Series G2RS Relay Type General Purpose Coil Type Non Latching Coil Current 87mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) Operate Time 15ms Release Time 20ms Features Diode, LED Indicator, Test Button Mounting Type Termination Style Plug In Report errors?		
Category Relays Power Relays, Over 2 Amps - Series G2RS Relay Type General Purpose Coil Type Non Latching Coil Current 87mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 15ms Release Time 20ms Features Diode, LED Indicator, Test Button Mounting Type Termination Style	Manufacturer Part Number	G2R-2-SNDI DC6(S)
Package Series G2RS Relay Type General Purpose Coil Type Non Latching Coil Current 87mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) Operate Time 15ms Release Time 20ms Features Diode, LED Indicator, Test Button Mounting Type Termination Style Plug In	Manufacturer	Omron Automation and Safety
Package - G2RS Relay Type General Purpose Coil Type Non Latching Coil Current 87mA Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 15ms Release Time 20ms Features Diode, LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Category	Relays
SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current87mACoil Voltage6VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.9 VDCOperate Time15msRelease Time20msFeaturesDiode, LED Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current87mACoil Voltage6VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.9 VDCOperate Time15msRelease Time20msFeaturesDiode, LED Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In	Package	-
Coil TypeNon LatchingCoil Current87mACoil Voltage6VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.9 VDCOperate Time15msRelease Time20msFeaturesDiode, LED Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In	Series	G2RS
Coil Current Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 15ms Release Time 20ms Features Diode, LED Indicator, Test Button Mounting Type Socketable Termination Style	Relay Type	General Purpose
Coil Voltage 6VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 15ms Release Time 20ms Features Diode, LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 15ms Release Time 20ms Features Diode, LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Coil Current	87mA
Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 15ms Release Time 20ms Features Diode, LED Indicator, Test Button Mounting Type Socketable Termination Style	Coil Voltage	6VDC
Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 15ms Release Time 20ms Features Diode, LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 15ms Release Time 20ms Features Diode, LED Indicator, Test Button Mounting Type Socketable Termination Style 4.2 VDC 0.9 VDC 15ms 20ms Plug In	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time 15ms Release Time 20ms Features Diode, LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Switching Voltage	380VAC, 125VDC - Max
Operate Time 15ms Release Time 20ms Features Diode, LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	4.2 VDC
Release Time 20ms Features Diode, LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	0.9 VDC
Features Diode, LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Operate Time	15ms
Mounting Type Socketable Termination Style Plug In	Release Time	20ms
Termination Style Plug In	Features	Diode, LED Indicator, Test Button
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

G2R-2-SNDI DC6(S) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G2R-2-SNDI DC6(S) Payment Methods



















G2R-2-SNDI DC6(S) Shipping Methods













If you have any question about G2R-2-SNDI DC6(S), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com