

G2R-2-SNI DC12(S) Information



For Reference Only

Part Number G2R-2-SNI DC12(S)

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 5A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G2R-2-SNI DC12(S) Specifications

Manufacturer Part Number G2R-2-SNI DC12(S) Manufacturer Omron Automation and Safety Category Relays Power Relays, Over 2 Amps Package - Series G2RS Relay Type General Purpose Coil Type Non Latching Coil Current 43.2mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 10ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current43.2mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time15msRelease Time10msFeaturesLED Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	G2R-2-SNI DC12(S)
Package-SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current43.2mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time15msRelease Time10msFeaturesLED Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In	Manufacturer	Omron Automation and Safety
Package-SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current43.2mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time15msRelease Time10msFeaturesLED Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In	Category	Relays
SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current43.2mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time15msRelease Time10msFeaturesLED Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 43.2mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 10ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current43.2mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time15msRelease Time10msFeaturesLED Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In	Series	G2RS
Coil Current 43.2mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 10ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Relay Type	General Purpose
Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 10ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 10ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Coil Current	43.2mA
Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 10ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Coil Voltage	12VDC
Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 10ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 10ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time 15ms Release Time 10ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Switching Voltage	380VAC, 125VDC - Max
Operate Time15msRelease Time10msFeaturesLED Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In	Turn On Voltage (Max)	8.4 VDC
Release Time 10ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	1.8 VDC
Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Operate Time	15ms
Mounting Type Socketable Termination Style Plug In	Release Time	10ms
Termination Style Plug In	Features	LED Indicator, Test Button
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

G2R-2-SNI DC12(S) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G2R-2-SNI DC12(S) Payment Methods



















G2R-2-SNI DC12(S) Shipping Methods













If you have any question about G2R-2-SNI DC12(S), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com