



G2R-24-AUL DC12 Information



For Reference Only

Part Number G2R-24-AUL DC12

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 4A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G2R-24-AUL DC12 Specifications

Manufacturer Part Number G2R-24-AUL DC12 Manufacturer Omron Electronics Inc-EMC Div Category Relays Power Relays, Over 2 Amps Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 43.6mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 4A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 5ms Features Sealed - Fully		
Category Relays Power Relays, Over 2 Amps Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 43.6mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 4A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 5ms	Manufacturer Part Number	G2R-24-AUL DC12
Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 43.6mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 4A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 5ms	Manufacturer	Omron Electronics Inc-EMC Div
Package - G2R Relay Type General Purpose Coil Type Non Latching Coil Current 43.6mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 4A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 5ms	Category	Relays
Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 43.6mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 4A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 5ms		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 43.6mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 4A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 5ms	Package	-
Coil Type Non Latching Coil Current 43.6mA Coil Voltage 12VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 4A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 5ms	Series	G2R
Coil Current43.6mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)4ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time15msRelease Time5ms	Relay Type	General Purpose
Coil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)4ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time15msRelease Time5ms	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 15ms Release Time 5ms	Coil Current	43.6mA
Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 5ms	Coil Voltage	12VDC
Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.8 VDC Operate Time 15ms Release Time 5ms	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 15ms Release Time 5ms	Contact Rating (Current)	4A
Turn Off Voltage (Min) Operate Time 1.8 VDC 15ms Release Time 5ms	Switching Voltage	380VAC, 125VDC - Max
Operate Time 15ms Release Time 5ms	Turn On Voltage (Max)	8.4 VDC
Release Time 5ms	Turn Off Voltage (Min)	1.8 VDC
	Operate Time	15ms
Features Sealed - Fully	Release Time	5ms
	Features	Sealed - Fully
Mounting Type Through Hole	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

G2R-24-AUL DC12 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G2R-24-AUL DC12 Payment Methods





















G2R-24-AUL DC12 Shipping Methods













If you have any question about G2R-24-AUL DC12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com