

G2R-24-T130 DC16

G2R-24-T130 DC16 Information



Number	G2R-24-T130 DC16	
ufacturer	Omron Electronics Inc-EMC Div	
gory	Relays Power Relays, Over 2 Amps	
ription	RELAY GEN PURPOSE DPDT 4A 16V	
age	-	
	For the pricing/inventory/lead time, please contact	
	us	
	Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



G2R-24-T130 DC16 Specifications

ManufacturerOmron Electronics Inc-EMC DivCategoryRelays Power Relays, Over 2 AmpsPackage-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.1mACoil VoltageIeVDCContact FormDPDT (2 Form C)Contact Rating (Current)380VAC, 125VDC - MaxSwitching Voltage (Max)11.2 VDCTurn Onf Voltage (Max)5msRelease TimeSmsFeaturesSmelMounting TypeThrough Hole		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.1mACoil VoltageIeVDC 1Contact FormDPDT (2 Form C)Contact Rating (Current)380VAC, 125VDC - MaxSwitching Voltage1.2 VDCTurn On Voltage (Max)1.2 VDCCurnent5.4 VDCSeleas TimeSmsRelease TimeSeled - FullyMounting TypeThrough Hole	Manufacturer Part Number	G2R-24-T130 DC16
Power Relays, Over 2 AmpsPackage-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.1mACoil Voltage16VDCContact FormDPDT (2 Form C)Contact Rating (Current)4ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)11.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time5msRelease TimeSealed - FullyMounting TypeThrough Hole	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.1mACoil Voltage16VDCContact FormDPDT (2 Form C)Contact Rating (Current)4ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)11.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough Hole	Category	Relays
SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.1mACoil Voltage16VDCContact FormDPDT (2 Form C)Contact Rating (Current)4ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)11.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time5msRelease TimeSealed - FullyMounting TypeThrough Hole		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.1mACoil Voltage16VDCContact FormDPDT (2 Form C)Contact Rating (Current)4ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)11.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough Hole	Package	-
Coil TypeNon LatchingCoil Current33.1mACoil Voltage16VDCContact FormDPDT (2 Form C)Contact Rating (Current)4ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)11.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough Hole	Series	G2R
Coil Current33.1mACoil Voltage16VDCContact FormDPDT (2 Form C)Contact Rating (Current)4ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)11.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough Hole	Relay Type	General Purpose
Contact Form16VDCContact FormDPDT (2 Form C)Contact Rating (Current)4ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)11.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough Hole	Coil Type	Non Latching
Contact FormDPDT (2 Form C)Contact Rating (Current)4ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)11.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough Hole	Coil Current	33.1mA
Contact Rating (Current)4ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)11.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough Hole	Coil Voltage	16VDC
Switching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)11.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough Hole	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)11.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough Hole	Contact Rating (Current)	4A
Turn Off Voltage (Min)2.4 VDCOperate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough Hole	Switching Voltage	380VAC, 125VDC - Max
Operate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough Hole	Turn On Voltage (Max)	11.2 VDC
Release Time5msFeaturesSealed - FullyMounting TypeThrough Hole	Turn Off Voltage (Min)	2.4 VDC
FeaturesSealed - FullyMounting TypeThrough Hole	Operate Time	15ms
Mounting Type Through Hole	Release Time	5ms
	Features	Sealed - Fully
Termination Style PC Pin	Mounting Type	Through Hole
	Termination Style	PC Pin
Report errors?		Report errors?

G2R-24-T130 DC16 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

G2R-24-T130 DC16 Payment Methods



G2R-24-T130 DC16 Shipping Methods



If you have any question about G2R-24-T130 DC16, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com