



G2R-2A4-ASI-DC24 Information



For Reference Only

Part Number G2R-2A4-ASI-DC24

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPST 4A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G2R-2A4-ASI-DC24 Specifications

Manufacturer Part Number G2R-2A4-ASI-DC24 Manufacturer Omron Electronics Inc-EMC Div Category Relays Power Relays, Over 2 Amps Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 21.8mA Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 4A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPackage-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current21.8mACoil Voltage24VDCContact FormDPST (2 Form A)Contact Rating (Current)4ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)3.6 VDCOperate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough Hole	Manufacturer Part Number	G2R-2A4-ASI-DC24
Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 21.8mA Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 4A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current21.8mACoil Voltage24VDCContact FormDPST (2 Form A)Contact Rating (Current)4ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)3.6 VDCOperate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough Hole	Category	Relays
SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current21.8mACoil Voltage24VDCContact FormDPST (2 Form A)Contact Rating (Current)4ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)3.6 VDCOperate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough Hole		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 21.8mA Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 4A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole	Package	-
Coil Type Non Latching Coil Current 21.8mA Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 4A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole	Series	G2R
Coil Current21.8mACoil Voltage24VDCContact FormDPST (2 Form A)Contact Rating (Current)4ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)3.6 VDCOperate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough Hole	Relay Type	General Purpose
Coil Voltage24VDCContact FormDPST (2 Form A)Contact Rating (Current)4ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)3.6 VDCOperate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough Hole	Coil Type	Non Latching
Contact Form DPST (2 Form A) Contact Rating (Current) 4A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole	Coil Current	21.8mA
Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole	Coil Voltage	24VDC
Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole	Contact Form	DPST (2 Form A)
Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole	Contact Rating (Current)	4A
Turn Off Voltage (Min) Operate Time 15ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole	Switching Voltage	380VAC, 125VDC - Max
Operate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough Hole	Turn On Voltage (Max)	16.8 VDC
Release Time 5ms Features Sealed - Fully Mounting Type Through Hole	Turn Off Voltage (Min)	3.6 VDC
Features Sealed - Fully Mounting Type Through Hole	Operate Time	15ms
Mounting Type Through Hole	Release Time	5ms
	Features	Sealed - Fully
Termination Style PC Pin	Mounting Type	Through Hole
	Termination Style	PC Pin
Report errors?		Report errors?

G2R-2A4-ASI-DC24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G2R-2A4-ASI-DC24 Payment Methods



















G2R-2A4-ASI-DC24 Shipping Methods













If you have any question about G2R-2A4-ASI-DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com