

G2R-2A4-DC6 Information

www.heisener.com

For Reference Only

Part Number G2R-2A4-DC6

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GENERAL PURPOSE DPST 4A 6V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G2R-2A4-DC6 Specifications

Manufacturer Part Number G2R-2A4-DC6 Manufacturer Omron Electronics Inc-EMC Div Category Relays Power Relays, Over 2 Amps - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 88.2mA Coil Voltage 6VDC Contact Form DPST (2 Form A) Contact Rating (Current) 4A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC
Category Relays Power Relays, Over 2 Amps Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 88.2mA Coil Voltage Contact Form DPST (2 Form A) Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max
Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 88.2mA Coil Voltage 6VDC Contact Form DPST (2 Form A) Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max
Package - G2R Relay Type General Purpose Coil Type Non Latching Coil Current 88.2mA Coil Voltage 6VDC Contact Form DPST (2 Form A) Contact Rating (Current) 4A Switching Voltage 380VAC, 125VDC - Max
Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 88.2mA Coil Voltage 6VDC Contact Form DPST (2 Form A) Contact Rating (Current) 4A Switching Voltage 380VAC, 125VDC - Max
Relay Type General Purpose Coil Type Non Latching Coil Current 88.2mA Coil Voltage 6VDC Contact Form DPST (2 Form A) Contact Rating (Current) 4A Switching Voltage 380VAC, 125VDC - Max
Coil Type Non Latching Coil Current 88.2mA Coil Voltage 6VDC Contact Form DPST (2 Form A) Contact Rating (Current) 4A Switching Voltage 380VAC, 125VDC - Max
Coil Current88.2mACoil Voltage6VDCContact FormDPST (2 Form A)Contact Rating (Current)4ASwitching Voltage380VAC, 125VDC - Max
Coil Voltage 6VDC Contact Form DPST (2 Form A) Contact Rating (Current) 4A Switching Voltage 380VAC, 125VDC - Max
Contact Form DPST (2 Form A) Contact Rating (Current) 4A Switching Voltage 380VAC, 125VDC - Max
Contact Rating (Current) Switching Voltage 4A 380VAC, 125VDC - Max
Switching Voltage 380VAC, 125VDC - Max
Turn On Voltage (Max) 4.2 VDC
Turn Off Voltage (Min) 0.9 VDC
Operate Time 15ms
Release Time 5ms
Features Sealed - Fully
Mounting Type Through Hole
Termination Style PC Pin
Report errors?

G2R-2A4-DC6 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G2R-2A4-DC6 Payment Methods



















G2R-2A4-DC6 Shipping Methods













If you have any question about G2R-2A4-DC6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com