



G2R-2A4-H-DC5 Information



For Reference Only

Part Number G2R-2A4-H-DC5

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GENERAL PURPOSE DPST 3A 5V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G2R-2A4-H-DC5 Specifications

Manufacturer Part Number G2R-2A4-H-DC5 Manufacturer Omron Electronics Inc-EMC Div Category Relays Power Relays, Over 2 Amps Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 71.4mA Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 3A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.75 VDC Operate Time 15ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current71.4mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)3ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.75 VDCOperate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G2R-2A4-H-DC5
Package-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current71.4mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)3ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.75 VDCOperate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 71.4mA Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 3A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.75 VDC Operate Time 15ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Category	Relays
SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current71.4mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)3ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.75 VDCOperate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 71.4mA Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 3A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.75 VDC Operate Time 15ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil TypeNon LatchingCoil Current71.4mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)3ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.75 VDCOperate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Series	G2R
Coil Current71.4mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)3ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.75 VDCOperate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Relay Type	General Purpose
Coil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)3ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.75 VDCOperate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Coil Type	Non Latching
Contact Form DPST (2 Form A) Contact Rating (Current) 3A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.75 VDC Operate Time 15ms Release Time 5ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Current	71.4mA
Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.75 VDC Operate Time 15ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style	Coil Voltage	5VDC
Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.75 VDC Operate Time 15ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style 380VAC, 125VDC - Max 3.5 VDC 0.75 VDC 15ms Formination Style	Contact Form	DPST (2 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 15ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style 3.5 VDC 0.75 VDC 0.75 VDC 15ms Forms Forms PC Pin	Contact Rating (Current)	3A
Turn Off Voltage (Min) Operate Time 15ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style 0.75 VDC 5ms Features PC Pin	Switching Voltage	380VAC, 125VDC - Max
Operate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	3.5 VDC
Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	0.75 VDC
Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Operate Time	15ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	Sealed - Fully
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

G2R-2A4-H-DC5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G2R-2A4-H-DC5 Payment Methods



















G2R-2A4-H-DC5 Shipping Methods













If you have any question about G2R-2A4-H-DC5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com