



G2RK-1-DC5 Information

Heisener.com

Part Number G2RK-1-DC5

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GENERAL PURPOSE SPDT 5A 5V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G2RK-1-DC5 Specifications

Manufacturer Part Number G2RK-1-DC5 Manufacturer Omron Electronics Inc-EMC Div Category Relays Power Relays, Over 2 Amps Package - Series G2R Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 167mA Coil Voltage 5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 20ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG2RRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current167mACoil Voltage5VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)-Operate Time20msRelease Time20msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G2RK-1-DC5
Package - G2R Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 167mA Coil Voltage 5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 20ms Features Sealed - Flux Protection Mounting Type Trinoul Coil Sear Relays, Over 2 Amps G2R Relays, Over 2 Amps Features Sealed - Supplementary G2R Features Features Sealed - Flux Protection Through Hole Termination Style	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG2RRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current167mACoil Voltage5VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)-Operate Time20msRelease Time20msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesG2RRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current167mACoil Voltage5VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)-Operate Time20msRelease Time20msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 167mA Coil Voltage 5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 20ms Release Time Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil Type Latching, Dual Coil Coil Current 167mA Coil Voltage 5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 20ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Series	G2R
Coil Current Coil Voltage 5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 20ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) - Operate Time 20ms Release Time 20ms Release Time 5eatures Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Type	Latching, Dual Coil
Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Release Time Sealed - Flux Protection Mounting Type Through Hole Termination Style	Coil Current	167mA
Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max 3.5 VDC Turn On Voltage (Max) - Operate Time 20ms Release Time 20ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style	Coil Voltage	5VDC
Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style 3.5 VDC 3.5 VDC	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	380VAC, 125VDC - Max
Operate Time20msRelease Time20msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	3.5 VDC
Release Time 20ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	-
Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Operate Time	20ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	20ms
Termination Style PC Pin	Features	Sealed - Flux Protection
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

G2RK-1-DC5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G2RK-1-DC5 Payment Methods



















G2RK-1-DC5 Shipping Methods













If you have any question about G2RK-1-DC5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com