

G2RL-1-E DC48 Information



For Reference Only

Part Number G2RL-1-E DC48

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPDT 16A 48V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G2RL-1-E DC48 Specifications

Manufacturer Part Number G2RL-1-E DC48 Manufacturer Omron Electronics Inc-EMC Div Category Relays Power Relays, Over 2 Amps Package - Series G2RL Relay Type General Purpose Coil Type Non Latching Coil Current 8.96mA Coil Voltage 48VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC, 300VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin		
Category Relays Power Relays, Over 2 Amps Package - Series G2RL Relay Type General Purpose Coil Type Non Latching Coil Current 8.96mA Coil Voltage 48VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC, 300VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Manufacturer Part Number	G2RL-1-E DC48
Package - Series G2RL Relay Type General Purpose Coil Type Non Latching Coil Current 8.96mA Coil Voltage 48VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC, 300VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package - Series G2RL Relay Type General Purpose Coil Type Non Latching Coil Current 8.96mA Coil Voltage 48VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC, 300VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Category	Relays
Series G2RL Relay Type General Purpose Coil Type Non Latching Coil Current 8.96mA Coil Voltage 48VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC, 300VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 8.96mA Coil Voltage 48VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC, 300VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 5ms Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil Type Non Latching Coil Current 8.96mA Coil Voltage 48VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC, 300VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Series	G2RL
Coil Current 8.96mA Coil Voltage 48VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC, 300VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 48VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC, 300VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 5ms Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) 16A Switching Voltage 440VAC, 300VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 5ms Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Current	8.96mA
Contact Rating (Current) Switching Voltage 440VAC, 300VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Voltage	48VDC
Switching Voltage 440VAC, 300VDC - Max Turn On Voltage (Max) 33.6 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	16A
Turn Off Voltage (Min) Operate Time 15ms Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	440VAC, 300VDC - Max
Operate Time 15ms Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	33.6 VDC
Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	4.8 VDC
Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Operate Time	15ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	Insulation - Class B, Sealed - Flux Protection
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

G2RL-1-E DC48 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G2RL-1-E DC48 Payment Methods



















G2RL-1-E DC48 Shipping Methods













If you have any question about G2RL-1-E DC48, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com