



### **G2RV-1-S DC11 Information**

www.

For Reference Only

Part Number G2RV-1-S DC11

Manufacturer Omron Automation and Safety

**Category** Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPDT 6A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **G2RV-1-S DC11 Specifications**

Manufacturer Part Number         G2RV-1-S DC11           Manufacturer         Omron Automation and Safety           Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         G2RV           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         27.2mA           Coil Voltage         12VDC           Contact Form         SPDT (1 Form C)           Contact Rating (Current)         6A           Switching Voltage         440VAC, 125VDC - Max           Turn On Voltage (Max)         9.6 VDC           Turn Off Voltage (Min)         1.2 VDC           Operate Time         20ms           Release Time         40ms           Features         -           Mounting Type         Socketable           Termination Style         Plue In		
Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         G2RV           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         27.2mA           Coil Voltage         12VDC           Contact Form         SPDT (1 Form C)           Contact Rating (Current)         6A           Switching Voltage         440VAC, 125VDC - Max           Turn On Voltage (Max)         9.6 VDC           Turn Off Voltage (Min)         1.2 VDC           Operate Time         20ms           Release Time         40ms           Features         -           Mounting Type         Socketable	Manufacturer Part Number	G2RV-1-S DC11
Package - Series G2RV Relay Type General Purpose Coil Type Non Latching Coil Current 27.2mA Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 6A Switching Voltage 440VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 40ms Features - Mounting Type Socketable	Manufacturer	Omron Automation and Safety
Package-SeriesG2RVRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current27.2mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)6ASwitching Voltage440VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time40msFeatures-Mounting TypeSocketable	Category	Relays
Series         G2RV           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         27.2mA           Coil Voltage         12VDC           Contact Form         SPDT (1 Form C)           Contact Rating (Current)         6A           Switching Voltage         440VAC, 125VDC - Max           Turn On Voltage (Max)         9.6 VDC           Turn Off Voltage (Min)         1.2 VDC           Operate Time         20ms           Release Time         40ms           Features         -           Mounting Type         Socketable		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 27.2mA Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 6A Switching Voltage 440VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 40ms Features - Mounting Type Socketable	Package	-
Coil TypeNon LatchingCoil Current27.2mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)6ASwitching Voltage440VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time40msFeatures-Mounting TypeSocketable	Series	G2RV
Coil Current 27.2mA  Coil Voltage 12VDC  Contact Form SPDT (1 Form C)  Contact Rating (Current) 6A  Switching Voltage 440VAC, 125VDC - Max  Turn On Voltage (Max) 9.6 VDC  Turn Off Voltage (Min) 1.2 VDC  Operate Time 20ms  Release Time 40ms  Features -  Mounting Type Socketable	Relay Type	General Purpose
Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 6A Switching Voltage 440VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 40ms Features - Mounting Type Socketable	Coil Type	Non Latching
Contact Form SPDT (1 Form C)  Contact Rating (Current)  Switching Voltage  440VAC, 125VDC - Max  Turn On Voltage (Max)  7urn Off Voltage (Min)  1.2 VDC  Operate Time  20ms  Release Time  40ms  Features  -  Mounting Type  Socketable	Coil Current	27.2mA
Contact Rating (Current)  Switching Voltage  440VAC, 125VDC - Max  Turn On Voltage (Max)  9.6 VDC  Turn Off Voltage (Min)  1.2 VDC  Operate Time  20ms  Release Time  40ms  Features  -  Mounting Type  Socketable	Coil Voltage	12VDC
Switching Voltage 440VAC, 125VDC - Max  Turn On Voltage (Max) 9.6 VDC  Turn Off Voltage (Min) 1.2 VDC  Operate Time 20ms  Release Time 40ms  Features -  Mounting Type Socketable	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max)  7 Turn Off Voltage (Min)  9.6 VDC  1.2 VDC  Operate Time  20ms  Release Time  40ms  Features  -  Mounting Type  Socketable	Contact Rating (Current)	6A
Turn Off Voltage (Min)  Operate Time  20ms  Release Time  40ms  Features  - Mounting Type  Socketable	Switching Voltage	440VAC, 125VDC - Max
Operate Time 20ms Release Time 40ms Features - Mounting Type Socketable	Turn On Voltage (Max)	9.6 VDC
Release Time 40ms Features - Mounting Type Socketable	Turn Off Voltage (Min)	1.2 VDC
Features - Mounting Type Socketable	Operate Time	20ms
Mounting Type Socketable	Release Time	40ms
	Features	-
Termination Style Plug In	Mounting Type	Socketable
1 lug lii	Termination Style	Plug In
Report errors?		Report errors?

#### **G2RV-1-S DC11 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **G2RV-1-S DC11 Payment Methods**



















## **G2RV-1-S DC11 Shipping Methods**













If you have any question about G2RV-1-S DC11, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com