



G2RV-SL700 AC/DC48 Information



For Reference Only

Part Number G2RV-SL700 AC/DC48

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPDT 6A 48V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G2RV-SL700 AC/DC48 Specifications

Manufacturer Part Number G2RV-SL700 AC/DC48 Manufacturer Omron Automation and Safety Category Relays Package - Series G2RV Relay Type General Purpose with Socket Coil Type Non Latching Coil Current 5.2mA Coil Voltage 48VAC/DC Contact Form SPDT (1 Form C) Contact Rating (Current) 6A Switching Voltage 440VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VAC/DC Turn Off Voltage (Min) 4.8 VAC/DC Operate Time 20ms Release Time 40ms Features - Mounting Type DIN Rail Termination Style Screw Terminal		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG2RVRelay TypeGeneral Purpose with SocketCoil TypeNon LatchingCoil Current5.2mACoil Voltage48VAC/DCContact FormSPDT (1 Form C)Contact Rating (Current)6ASwitching Voltage440VAC, 125VDC - MaxTurn On Voltage (Max)38.4 VAC/DCTurn Off Voltage (Min)4.8 VAC/DCOperate Time20msRelease Time40msFeatures-Mounting TypeDIN RailTermination StyleScrew Terminal	Manufacturer Part Number	G2RV-SL700 AC/DC48
Package - Series G2RV Relay Type General Purpose with Socket Coil Type Non Latching Coil Current 5.2mA Coil Voltage 48VAC/DC Contact Form SPDT (1 Form C) Contact Rating (Current) 6A Switching Voltage 440VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VAC/DC Turn Off Voltage (Min) 4.8 VAC/DC Operate Time 20ms Release Time 40ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Manufacturer	Omron Automation and Safety
Package - Series G2RV Relay Type General Purpose with Socket Coil Type Non Latching Coil Current 5.2mA Coil Voltage 48VAC/DC Contact Form SPDT (1 Form C) Contact Rating (Current) 6A Switching Voltage 440VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VAC/DC Turn Off Voltage (Min) 4.8 VAC/DC Operate Time 20ms Release Time 40ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Category	Relays
SeriesG2RVRelay TypeGeneral Purpose with SocketCoil TypeNon LatchingCoil Current5.2mACoil Voltage48VAC/DCContact FormSPDT (1 Form C)Contact Rating (Current)6ASwitching Voltage440VAC, 125VDC - MaxTurn On Voltage (Max)38.4 VAC/DCTurn Off Voltage (Min)4.8 VAC/DCOperate Time20msRelease Time40msFeatures-Mounting TypeDIN RailTermination StyleScrew Terminal		Power Relays, Over 2 Amps
Relay Type General Purpose with Socket Coil Type Non Latching Coil Current 5.2mA Coil Voltage 48VAC/DC Contact Form SPDT (1 Form C) Contact Rating (Current) 6A Switching Voltage 440VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VAC/DC Turn Off Voltage (Min) 4.8 VAC/DC Operate Time 20ms Release Time 40ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Package	-
Coil TypeNon LatchingCoil Current5.2mACoil Voltage48VAC/DCContact FormSPDT (1 Form C)Contact Rating (Current)6ASwitching Voltage440VAC, 125VDC - MaxTurn On Voltage (Max)38.4 VAC/DCTurn Off Voltage (Min)4.8 VAC/DCOperate Time20msRelease Time40msFeatures-Mounting TypeDIN RailTermination StyleScrew Terminal	Series	G2RV
Coil Current Coil Voltage 48VAC/DC Contact Form SPDT (1 Form C) Contact Rating (Current) 6A Switching Voltage 440VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VAC/DC Turn Off Voltage (Min) 4.8 VAC/DC Operate Time 20ms Release Time 40ms Features - Mounting Type DIN Rail Termination Style	Relay Type	General Purpose with Socket
Coil Voltage 48VAC/DC Contact Form SPDT (1 Form C) Contact Rating (Current) 6A Switching Voltage 440VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VAC/DC Turn Off Voltage (Min) 4.8 VAC/DC Operate Time 20ms Release Time 40ms Features - Mounting Type DIN Rail Termination Style SPDT (1 Form C)	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) 6A Switching Voltage 440VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VAC/DC Turn Off Voltage (Min) 4.8 VAC/DC Operate Time 20ms Release Time 40ms Features - Mounting Type DIN Rail Termination Style Serew Terminal	Coil Current	5.2mA
Contact Rating (Current) Switching Voltage 440VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VAC/DC Turn Off Voltage (Min) 4.8 VAC/DC Operate Time 20ms Release Time 40ms Features - Mounting Type DIN Rail Termination Style	Coil Voltage	48VAC/DC
Switching Voltage 440VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VAC/DC Turn Off Voltage (Min) 4.8 VAC/DC Operate Time 20ms Release Time 40ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) 4.8 VAC/DC Operate Time 20ms Release Time 40ms Features - Mounting Type DIN Rail Termination Style 38.4 VAC/DC 4.8 VAC/DC DIN Rail Screw Terminal	Contact Rating (Current)	6A
Turn Off Voltage (Min) Operate Time 20ms Release Time 40ms Features Mounting Type DIN Rail Termination Style Screw Terminal	Switching Voltage	440VAC, 125VDC - Max
Operate Time 20ms Release Time 40ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Turn On Voltage (Max)	38.4 VAC/DC
Release Time 40ms Features - Mounting Type DIN Rail Termination Style Screw Terminal	Turn Off Voltage (Min)	4.8 VAC/DC
Features - Mounting Type DIN Rail Termination Style Screw Terminal	Operate Time	20ms
Mounting Type DIN Rail Termination Style Screw Terminal	Release Time	40ms
Termination Style Screw Terminal	Features	-
	Mounting Type	DIN Rail
Report errors?	Termination Style	Screw Terminal
		Report errors?

G2RV-SL700 AC/DC48 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G2RV-SL700 AC/DC48 Payment Methods



















G2RV-SL700 AC/DC48 Shipping Methods













If you have any question about G2RV-SL700 AC/DC48, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com