

## G2RV-SR500-AP AC/DC48

### G2RV-SR500-AP AC/DC48 Information



For Reference Only

Part Number G2RV-SR500-AP AC/DC48

Manufacturer Omron Automation and Safety

**Category** Relays

Signal Relays, Up to 2 Amps

**Description** RELAY GEN PURPOSE SPDT 50MA 48V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **G2RV-SR500-AP AC/DC48 Specifications**

Manufacturer Part Number       G2RV-SR500-AP AC/DC48         Manufacturer       Omron Automation and Safety         Category       Relays         Signal Relays, Up to 2 Amps         Package       -         Series       G2RV-SR         Relay Type       General Purpose with Socket         Coil Type       Non Latching         Coil Current       6.1mA         Coil Voltage       48VAC/DC         Contact Form       SPDT (1 Form C)         Contact Rating (Current)       50mA         Switching Voltage       30VAC, 36VDC - Max         Turn On Voltage (Max)       38.4 VAC/DC         Turn Off Voltage (Min)       4.8 VAC/DC         Operate Time       20ms         Release Time       40ms         Features       -         Mounting Type       DIN Rail         Termination Style       Screwless Clamp		
Category Relays Signal Relays, Up to 2 Amps  Package - Series G2RV-SR Relay Type General Purpose with Socket Coil Type Non Latching Coil Current 6.1mA Coil Voltage 48VAC/DC Contact Form SPDT (1 Form C) Contact Rating (Current) 50mA Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 38.4 VAC/DC Turn Off Voltage (Min) 4.8 VAC/DC Operate Time 20ms Release Time 40ms Features - Mounting Type DIN Rail Termination Style	Manufacturer Part Number	G2RV-SR500-AP AC/DC48
Package-SeriesG2RV-SRRelay TypeGeneral Purpose with SocketCoil TypeNon LatchingCoil Current6.1mACoil Voltage48VAC/DCContact FormSPDT (1 Form C)Contact Rating (Current)50mASwitching Voltage30VAC, 36VDC - MaxTurn On Voltage (Max)38.4 VAC/DCTurn Off Voltage (Min)4.8 VAC/DCOperate Time20msRelease Time40msFeatures-Mounting TypeDIN RailTermination StyleScrewless Clamp	Manufacturer	Omron Automation and Safety
Package         -           Series         G2RV-SR           Relay Type         General Purpose with Socket           Coil Type         Non Latching           Coil Current         6.1 mA           Coil Voltage         48VAC/DC           Contact Form         SPDT (1 Form C)           Contact Rating (Current)         50mA           Switching Voltage         30VAC, 36VDC - Max           Turn On Voltage (Max)         38.4 VAC/DC           Turn Off Voltage (Min)         4.8 VAC/DC           Operate Time         20ms           Release Time         40ms           Features         -           Mounting Type         DIN Rail           Termination Style         Screwless Clamp	Category	Relays
SeriesG2RV-SRRelay TypeGeneral Purpose with SocketCoil TypeNon LatchingCoil Current6.1mACoil Voltage48VAC/DCContact FormSPDT (1 Form C)Contact Rating (Current)50mASwitching Voltage30VAC, 36VDC - MaxTurn On Voltage (Max)38.4 VAC/DCTurn Off Voltage (Min)4.8 VAC/DCOperate Time20msRelease Time40msFeatures-Mounting TypeDIN RailTermination StyleScrewless Clamp		Signal Relays, Up to 2 Amps
Relay Type General Purpose with Socket Coil Type Non Latching Coil Current 6.1mA Coil Voltage 48VAC/DC Contact Form SPDT (1 Form C) Contact Rating (Current) 50mA Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 38.4 VAC/DC Turn Off Voltage (Min) 4.8 VAC/DC Operate Time 20ms Release Time 40ms Features - Mounting Type DIN Rail Termination Style Screwless Clamp	Package	-
Coil TypeNon LatchingCoil Current6.1mACoil Voltage48VAC/DCContact FormSPDT (1 Form C)Contact Rating (Current)50mASwitching Voltage30VAC, 36VDC - MaxTurn On Voltage (Max)38.4 VAC/DCTurn Off Voltage (Min)4.8 VAC/DCOperate Time20msRelease Time40msFeatures-Mounting TypeDIN RailTermination StyleScrewless Clamp	Series	G2RV-SR
Coil Current Coil Voltage 48VAC/DC Contact Form SPDT (1 Form C) Contact Rating (Current) 50mA Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 38.4 VAC/DC Turn Off Voltage (Min) 4.8 VAC/DC Operate Time 20ms Release Time 40ms Features - Mounting Type DIN Rail Termination Style SPDT (1 Form C)	Relay Type	General Purpose with Socket
Coil Voltage 48VAC/DC Contact Form SPDT (1 Form C) Contact Rating (Current) 50mA Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 38.4 VAC/DC Turn Off Voltage (Min) 4.8 VAC/DC Operate Time 20ms Release Time 40ms Features - Mounting Type DIN Rail Termination Style Screwless Clamp	Coil Type	Non Latching
Contact Form SPDT (1 Form C)  Contact Rating (Current) 50mA  Switching Voltage 30VAC, 36VDC - Max  Turn On Voltage (Max) 38.4 VAC/DC  Turn Off Voltage (Min) 4.8 VAC/DC  Operate Time 20ms  Release Time 40ms  Features - Mounting Type DIN Rail  Termination Style Screwless Clamp	Coil Current	6.1mA
Contact Rating (Current)  Switching Voltage  30VAC, 36VDC - Max  Turn On Voltage (Max)  38.4 VAC/DC  Turn Off Voltage (Min)  4.8 VAC/DC  Operate Time  20ms  Release Time  40ms  Features  -  Mounting Type  DIN Rail  Termination Style  Screwless Clamp	Coil Voltage	48VAC/DC
Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 38.4 VAC/DC Turn Off Voltage (Min) 4.8 VAC/DC Operate Time 20ms Release Time 40ms Features - Mounting Type DIN Rail Termination Style Screwless Clamp	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  4.8 VAC/DC  Operate Time  20ms  Release Time  40ms  Features  -  Mounting Type  DIN Rail  Termination Style  38.4 VAC/DC  4.8 VAC/DC  DIN Rail  Screwless Clamp	Contact Rating (Current)	50mA
Turn Off Voltage (Min)  4.8 VAC/DC  Operate Time  20ms  Release Time  40ms  Features  -  Mounting Type  DIN Rail  Termination Style  Screwless Clamp	Switching Voltage	30VAC, 36VDC - Max
Operate Time 20ms Release Time 40ms Features - Mounting Type DIN Rail Termination Style Screwless Clamp	Turn On Voltage (Max)	38.4 VAC/DC
Release Time 40ms  Features - Mounting Type DIN Rail  Termination Style Screwless Clamp	Turn Off Voltage (Min)	4.8 VAC/DC
Features - Mounting Type DIN Rail Termination Style Screwless Clamp	Operate Time	20ms
Mounting Type DIN Rail Termination Style Screwless Clamp	Release Time	40ms
Termination Style Screwless Clamp	Features	-
	Mounting Type	DIN Rail
Report errors?	Termination Style	Screwless Clamp
		Report errors?

#### G2RV-SR500-AP AC/DC48 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### G2RV-SR500-AP AC/DC48 Payment Methods



















## G2RV-SR500-AP AC/DC48 Shipping Methods













If you have any question about G2RV-SR500-AP AC/DC48, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com