

G2RV-SR500-AP AC230

G2RV-SR500-AP AC230 Information



For Reference Only

Part Number G2RV-SR500-AP AC230
Manufacturer Omron Automation and Safety

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GEN PURPOSE SPDT 50MA 230V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G2RV-SR500-AP AC230 Specifications

| Manufacturer Part Number G2RV-SR500-AP AC230 Manufacturer Omron Automation and Safety Category Relays Signal Relays, Up to 2 Amps Package - Series G2RV-SR Relay Type General Purpose with Socket Coil Type Non Latching Coil Current 4.5mA Coil Voltage 230VAC Contact Form SPDT (1 Form C) Contact Rating (Current) 50mA Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 184 VAC Turn Off Voltage (Min) 23 VAC Operate Time 20ms Release Time 40ms Features - Mounting Type DIN Rail Termination Style Screwless Clamp | | |
|--|--------------------------|-----------------------------|
| Category Relays Signal Relays, Up to 2 Amps Package - Series G2RV-SR Relay Type General Purpose with Socket Coil Type Non Latching Coil Current 4.5mA Coil Voltage 230VAC Contact Form SPDT (1 Form C) Contact Rating (Current) 50mA Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 184 VAC Turn Off Voltage (Min) 23 VAC Operate Time 20ms Release Time 40ms Features - Mounting Type DIN Rail Termination Style Series Signal Relays Signal Relay Signal Relays Signal Relay Signal Signal Signal Relays Signal Signal Signal Relay Signal Signal Signal Relay Signal Sign | Manufacturer Part Number | G2RV-SR500-AP AC230 |
| Package-SeriesG2RV-SRRelay TypeGeneral Purpose with SocketCoil TypeNon LatchingCoil Current4.5mACoil Voltage230VACContact FormSPDT (1 Form C)Contact Rating (Current)50mASwitching Voltage30VAC, 36VDC - MaxTurn On Voltage (Max)184 VACTurn Off Voltage (Min)23 VACOperate Time20msRelease Time40msFeatures-Mounting TypeDIN RailTermination StyleScrewless Clamp | Manufacturer | Omron Automation and Safety |
| Package - Series G2RV-SR Relay Type General Purpose with Socket Coil Type Non Latching Coil Current 4.5mA Coil Voltage 230VAC Contact Form SPDT (1 Form C) Contact Rating (Current) 50mA Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 184 VAC Turn Off Voltage (Min) 23 VAC Operate Time 20ms Release Time 40ms Features - Mounting Type DIN Rail Termination Style Screwless Clamp | Category | Relays |
| SeriesG2RV-SRRelay TypeGeneral Purpose with SocketCoil TypeNon LatchingCoil Current4.5mACoil Voltage230VACContact FormSPDT (1 Form C)Contact Rating (Current)50mASwitching Voltage30VAC, 36VDC - MaxTurn On Voltage (Max)184 VACTurn Off Voltage (Min)23 VACOperate Time20msRelease Time40msFeatures-Mounting TypeDIN RailTermination StyleScrewless Clamp | | Signal Relays, Up to 2 Amps |
| Relay Type General Purpose with Socket Coil Type Non Latching Coil Current 4.5mA Coil Voltage 230VAC Contact Form SPDT (1 Form C) Contact Rating (Current) 50mA Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 184 VAC Turn Off Voltage (Min) 23 VAC Operate Time 20ms Release Time 40ms Features Mounting Type DIN Rail Termination Style Screwless Clamp | Package | - |
| Coil TypeNon LatchingCoil Current4.5mACoil Voltage230VACContact FormSPDT (1 Form C)Contact Rating (Current)50mASwitching Voltage30VAC, 36VDC - MaxTurn On Voltage (Max)184 VACTurn Off Voltage (Min)23 VACOperate Time20msRelease Time40msFeatures-Mounting TypeDIN RailTermination StyleScrewless Clamp | Series | G2RV-SR |
| Coil Current 4.5mA Coil Voltage 230VAC Contact Form SPDT (1 Form C) Contact Rating (Current) 50mA Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 184 VAC Turn Off Voltage (Min) 23 VAC Operate Time 20ms Release Time 40ms Features Mounting Type DIN Rail Termination Style SPDT (1 Form C) | Relay Type | General Purpose with Socket |
| Coil Voltage 230VAC Contact Form SPDT (1 Form C) Contact Rating (Current) 50mA Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 184 VAC Turn Off Voltage (Min) 23 VAC Operate Time 20ms Release Time 40ms Features - Mounting Type DIN Rail Termination Style Servel as Servel as Clamp | Coil Type | Non Latching |
| Contact Form SPDT (1 Form C) Contact Rating (Current) 50mA Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 184 VAC Turn Off Voltage (Min) 23 VAC Operate Time 20ms Release Time 40ms Features | Coil Current | 4.5mA |
| Contact Rating (Current) Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 184 VAC Turn Off Voltage (Min) 23 VAC Operate Time 20ms Release Time 40ms Features - Mounting Type DIN Rail Termination Style | Coil Voltage | 230VAC |
| Switching Voltage 30VAC, 36VDC - Max Turn On Voltage (Max) 184 VAC Turn Off Voltage (Min) 23 VAC Operate Time 20ms Release Time 40ms Features - Mounting Type DIN Rail Termination Style Screwless Clamp | Contact Form | SPDT (1 Form C) |
| Turn On Voltage (Max) 184 VAC Turn Off Voltage (Min) 23 VAC Operate Time 20ms Release Time 40ms Features - Mounting Type DIN Rail Termination Style Screwless Clamp | Contact Rating (Current) | 50mA |
| Turn Off Voltage (Min) 23 VAC Operate Time 20ms Release Time 40ms Features - Mounting Type DIN Rail Termination Style Screwless Clamp | Switching Voltage | 30VAC, 36VDC - Max |
| Operate Time 20ms Release Time 40ms Features - Mounting Type DIN Rail Termination Style Screwless Clamp | Turn On Voltage (Max) | 184 VAC |
| Release Time 40ms Features - Mounting Type DIN Rail Termination Style Screwless Clamp | Turn Off Voltage (Min) | 23 VAC |
| Features - Mounting Type DIN Rail Termination Style Screwless Clamp | Operate Time | 20ms |
| Mounting Type DIN Rail Termination Style Screwless Clamp | Release Time | 40ms |
| Termination Style Screwless Clamp | Features | - |
| | Mounting Type | DIN Rail |
| Report errors? | Termination Style | Screwless Clamp |
| | | Report errors? |

G2RV-SR500-AP AC230 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G2RV-SR500-AP AC230 Payment Methods



















G2RV-SR500-AP AC230 Shipping Methods













If you have any question about G2RV-SR500-AP AC230, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com