

G3T12AP-S Information

www...com

For Reference Only

Part Number G3T12AP-S
Manufacturer NKK Switches
Category Switches

Toggle Switches

Description SWITCH TOGGLE SPDT 0.4VA 28V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G3T12AP-S Specifications

Manufacturer Category Switches Package - Series G3T Circuit SPDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC Voltage Rating - DC Actuator Type Standard Round Actuator Length Illumination Illumination Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Surface Mount Termination Style Panel Cutout Dimensions Bushing Thread Ingress Protection Features NKK Switches Switches Switches Switches Switches Switches Switches On-Ke Switches SupDT Standard On-On On-On On-On On-On On-On On-On On-On On-On SPDT SPDT SPDT SPDT SPDT SPDT SPDT SPDT		
Category Switches Package - Series G3T Circuit SPDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 28V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 3.81mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Surface Mount Termination Style Gull Wing Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Process Sealed	Manufacturer Part Number	G3T12AP-S
Toggle Switches	Manufacturer	NKK Switches
Package - G3T Circuit SPDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 28V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 3.81mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Surface Mount Termination Style Gull Wing Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Process Sealed	Category	Switches
Series G3T Circuit SPDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 28V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 3.81mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Surface Mount Termination Style Gull Wing Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Process Sealed		Toggle Switches
Circuit SPDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 28V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 3.81mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Surface Mount Termination Style Gull Wing Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Process Sealed	Package	-
Switch Function Current Rating 0.4VA (AC/DC) Voltage Rating - AC 28V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 3.81mm Illumination Illumination Type, Color	Series	G3T
Current Rating 0.4VA (AC/DC) Voltage Rating - AC 28V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 3.81mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Surface Mount Termination Style Gull Wing Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Process Sealed	Circuit	SPDT
Voltage Rating - AC Voltage Rating - DC Actuator Type Standard Round 3.81mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Surface Mount Termination Style Panel Cutout Dimensions Bushing Thread Ingress Protection Features Process Sealed	Switch Function	On-On
Voltage Rating - DC Actuator Type Standard Round Actuator Length 3.81mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Surface Mount Termination Style Gull Wing Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection Features Process Sealed	Current Rating	0.4VA (AC/DC)
Actuator Type Actuator Length 3.81mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Surface Mount Termination Style Panel Cutout Dimensions Bushing Thread Ingress Protection Features Standard Round Gull Wing	Voltage Rating - AC	28V
Actuator Length Illumination Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Surface Mount Termination Style Panel Cutout Dimensions - Bushing Thread Ingress Protection Features 3.81mm Non-Illuminated - Unthreaded Process Sealed	Voltage Rating - DC	28V
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Surface Mount Gull Wing Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Process Sealed	Actuator Type	Standard Round
Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Surface Mount Termination Style Panel Cutout Dimensions Bushing Thread Ingress Protection Features	Actuator Length	3.81mm
Illumination Voltage (Nominal)-Mounting TypeSurface MountTermination StyleGull WingPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesProcess Sealed	Illumination	Non-Illuminated
Mounting TypeSurface MountTermination StyleGull WingPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesProcess Sealed	Illumination Type, Color	-
Termination Style Gull Wing Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Process Sealed	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Process Sealed	Mounting Type	Surface Mount
Bushing Thread Unthreaded Ingress Protection - Features Process Sealed	Termination Style	Gull Wing
Ingress Protection - Features Process Sealed	Panel Cutout Dimensions	-
Features Process Sealed	Bushing Thread	Unthreaded
	Ingress Protection	-
Papart arrors 9	Features	Process Sealed
Report errors:		Report errors?

G3T12AP-S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G3T12AP-S Payment Methods



















G3T12AP-S Shipping Methods













If you have any question about G3T12AP-S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com