

Heisener.com

G4D-212P-US-TV2-DC24

G4D-212P-US-TV2-DC24 Information

Part Number G4D-212P-US-TV2-DC24

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 5A 24V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G4D-212P-US-TV2-DC24 Specifications

Manufacturer Part Number G4D-212P-US-TV2-DC24 Manufacturer Omron Electronics Inc-EMC Div Category Relays Power Relays, Over 2 Amps - Series G4D Relay Type General Purpose Coil Type - Coil Current - Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPackage-SeriesG4DRelay TypeGeneral PurposeCoil Type-Coil Current-Coil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G4D-212P-US-TV2-DC24
Package - Series G4D Relay Type General Purpose Coil Type - Coil Current - Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Through Hole Termination Style PC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG4DRelay TypeGeneral PurposeCoil Type-Coil Current-Coil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesG4DRelay TypeGeneral PurposeCoil Type-Coil Current-Coil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type Coil Type - Coil Current - Coil Voltage Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) Operate Time Release Time Features Mounting Type Through Hole Termination Style General Purpose General Purpose General Purpose General Purpose General Purpose General Purpose General Purpose General Purpose General Purpose General Purpose	Package	-
Coil Type Coil Current Coil Voltage Contact Form DPDT (2 Form C) Contact Rating (Current) SA Switching Voltage 250VAC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time Features Mounting Type Through Hole Termination Style - Contact Rating (Current) SA DPDT (2 Form C)	Series	G4D
Coil Current Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time Release Time - Features - Mounting Type Through Hole Termination Style - POPDT (2 Form C)	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Through Hole Termination Style PC Pin	Coil Type	-
Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Through Hole Termination Style PC Pin	Coil Current	-
Contact Rating (Current) Switching Voltage 250VAC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) Operate Time Release Time - Release Time Features Mounting Type Through Hole Termination Style 5A 250VAC - Max - Turn On Voltage (Max) - Turn Off Voltage (Min)	Coil Voltage	24VDC
Switching Voltage 250VAC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time - Reatures Mounting Type Through Hole Termination Style 250VAC - Max - Turn Off Voltage (Max) - Turn Off Voltage (Min) - Through Hole PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time - Retures Mounting Type Through Hole Termination Style - Control of Voltage (Max) - Turn Off Voltage (Max) - Turn Off Voltage (Max) - Through Hole PC Pin	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time - Release Time - Features - Mounting Type Through Hole Termination Style - CONTROLL CONTROL	Switching Voltage	250VAC - Max
Operate Time - Release Time	Turn On Voltage (Max)	-
Release Time - Features - Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	-
Features - Mounting Type Through Hole Termination Style PC Pin	Operate Time	-
Mounting Type Through Hole Termination Style PC Pin	Release Time	-
Termination Style PC Pin	Features	-
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

G4D-212P-US-TV2-DC24 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G4D-212P-US-TV2-DC24 Payment Methods



















G4D-212P-US-TV2-DC24 Shipping Methods













If you have any question about G4D-212P-US-TV2-DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com