

G4Q-211A DC24 Information

Heisener.com

Part Number G4Q-211A DC24

Manufacturer Omron Automation and Safety

Category

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 5A 24V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G4Q-211A DC24 Specifications

Manufacturer Part Number G4Q-211A DC24 Manufacturer Omron Automation and Safety Category Relays Power Relays, Over 2 Amps Package - Series G4Q Relay Type General Purpose Coil Type Non Latching Coil Current 162mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 60ms Release Time - Features - Mounting Type Chassis Mount Termination Style Solder Lug		
Category Relays Power Relays, Over 2 Amps Package - Series G4Q Relay Type General Purpose Coil Type Non Latching Coil Current 162mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 60ms Release Time - Features - Mounting Type Chassis Mount Termination Style Solder Lug	Manufacturer Part Number	G4Q-211A DC24
Package-SeriesG4QRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current162mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)2.4 VDCOperate Time60msRelease Time-Features-Mounting TypeChassis MountTermination StyleSolder Lug	Manufacturer	Omron Automation and Safety
Package - Series G4Q Relay Type General Purpose Coil Type Non Latching Coil Current 162mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 60ms Release Time - Features - Mounting Type Chassis Mount Termination Style Solder Lug	Category	Relays
Series G4Q Relay Type General Purpose Coil Type Non Latching Coil Current 162mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 60ms Release Time - Features - Mounting Type Chassis Mount Termination Style Solder Lug		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current162mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)2.4 VDCOperate Time60msRelease Time-Features-Mounting TypeChassis MountTermination StyleSolder Lug	Package	-
Coil TypeNon LatchingCoil Current162mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)2.4 VDCOperate Time60msRelease Time-Features-Mounting TypeChassis MountTermination StyleSolder Lug	Series	G4Q
Coil Current162mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 250VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)2.4 VDCOperate Time60msRelease Time-Features-Mounting TypeChassis MountTermination StyleSolder Lug	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 60ms Release Time - Features - Mounting Type Chassis Mount Termination Style SA	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 60ms Release Time - Features - Mounting Type Chassis Mount Termination Style	Coil Current	162mA
Contact Rating (Current) Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 60ms Release Time - Features - Mounting Type Chassis Mount Termination Style	Coil Voltage	24VDC
Switching Voltage 250VAC, 250VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 60ms Release Time - Features - Mounting Type Chassis Mount Termination Style Solder Lug	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 60ms Release Time - Features - Mounting Type Chassis Mount Termination Style Solder Lug	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time 60ms Release Time - Features - Mounting Type Chassis Mount Termination Style Solder Lug	Switching Voltage	250VAC, 250VDC - Max
Operate Time 60ms Release Time - Features - Mounting Type Chassis Mount Termination Style Solder Lug	Turn On Voltage (Max)	16.8 VDC
Release Time	Turn Off Voltage (Min)	2.4 VDC
Features - Chassis Mount Termination Style Solder Lug	Operate Time	60ms
Mounting Type Chassis Mount Termination Style Solder Lug	Release Time	-
Termination Style Solder Lug	Features	-
	Mounting Type	Chassis Mount
Report errors?	Termination Style	Solder Lug
		Report errors?

G4Q-211A DC24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G4Q-211A DC24 Payment Methods



















G4Q-211A DC24 Shipping Methods













If you have any question about G4Q-211A DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com