

G4W-2214P-US-T130-DC24

G4W-2214P-US-T130-DC24 Information



For Reference Only

Part Number G4W-2214P-US-T130-DC24

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPST 15A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G4W-2214P-US-T130-DC24 Specifications

Manufacturer Part Number Manufacturer Omron Electronics Inc-EMC Div Relays Power Relays, Over 2 Amps Package Series G4W Relay Type General Purpose Coil Current 33.3mA Coil Voltage Contact Form DPST (2 Form A) Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Description: Gmen Alexandre Gawana and a company of the co		
CategoryRelays Power Relays, Over 2 AmpsPackage-SeriesG4WRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage24VDCContact FormDPST (2 Form A)Contact Rating (Current)15ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time20ms	Manufacturer Part Number	G4W-2214P-US-T130-DC24
Package - Series G4W Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 20ms	Manufacturer	Omron Electronics Inc-EMC Div
Package - G4W Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 20ms	Category	Relays
Series G4W Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 20ms		Power Relays, Over 2 Amps
Relay Type Coil Type Non Latching Coil Current 33.3mA Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 20ms	Package	-
Coil Type Non Latching Coil Current 33.3mA Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 20ms	Series	G4W
Coil Current33.3mACoil Voltage24VDCContact FormDPST (2 Form A)Contact Rating (Current)15ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time20ms	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 20ms	Coil Type	Non Latching
Contact Form DPST (2 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 20ms	Coil Current	33.3mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 20ms	Coil Voltage	24VDC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 20ms	Contact Form	DPST (2 Form A)
Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 20ms	Contact Rating (Current)	15A
Turn Off Voltage (Min) Operate Time 2.4 VDC 20ms	Switching Voltage	250VAC, 125VDC - Max
Operate Time 20ms	Turn On Voltage (Max)	19.2 VDC
1	Turn Off Voltage (Min)	2.4 VDC
Dalaca Tima	Operate Time	20ms
Release Time 5ms	Release Time	5ms
Features -	Features	-
Mounting Type Through Hole	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

G4W-2214P-US-T130-DC24 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G4W-2214P-US-T130-DC24 Payment Methods

































If you have any question about G4W-2214P-US-T130-DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com