



### **G5AK-237P-DC24 Information**

Heisener.com

Part Number G5AK-237P-DC24

Manufacturer Omron Electronics Inc-EMC Div

**Category** Relays

Signal Relays, Up to 2 Amps

**Description** RELAY GEN PURPOSE DPDT 1A 24V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **G5AK-237P-DC24 Specifications**

Manufacturer Part Number  Manufacturer  Omron Electronics Inc-EMC Div  Relays  Signal Relays, Up to 2 Amps  Package  - Series  G5A  Relay Type  General Purpose  Coil Type  Latching, Dual Coil  Coil Current  8.3mA  Coil Voltage  Contact Form  DPDT (2 Form C)  Contact Rating (Current)  1A  Switching Voltage  19.2 VDC
Category Relays Signal Relays, Up to 2 Amps Package - Series G5A Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 8.3mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 125VAC, 125VDC - Max
Package - Series G5A Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 8.3mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 125VAC, 125VDC - Max
Package - G5A  Relay Type General Purpose  Coil Type Latching, Dual Coil  Coil Current 8.3mA  Coil Voltage 24VDC  Contact Form DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage 125VAC, 125VDC - Max
Series G5A  Relay Type General Purpose  Coil Type Latching, Dual Coil  Coil Current 8.3mA  Coil Voltage 24VDC  Contact Form DPDT (2 Form C)  Contact Rating (Current) 1A  Switching Voltage 125VAC, 125VDC - Max
Relay Type Coil Type Latching, Dual Coil Coil Current 8.3mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 125VAC, 125VDC - Max
Coil Type Latching, Dual Coil Coil Current 8.3mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 125VDC - Max
Coil Current8.3mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 125VDC - Max
Coil Voltage 24VDC  Contact Form DPDT (2 Form C)  Contact Rating (Current) 1A  Switching Voltage 125VAC, 125VDC - Max
Contact Form DPDT (2 Form C) Contact Rating (Current)  Switching Voltage 125VAC, 125VDC - Max
Contact Rating (Current)  Switching Voltage  1A  125VAC, 125VDC - Max
Switching Voltage 125VAC, 125VDC - Max
Turn On Voltage (May)
Turn On Voltage (Max) 19.2 VDC
Turn Off Voltage (Min)
Operate Time 5ms
Release Time 5ms
Features -
Mounting Type Through Hole
Termination Style PC Pin
Report errors?

### **G5AK-237P-DC24 Guarantees**



## **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **G5AK-237P-DC24 Payment Methods**



















# **G5AK-237P-DC24** Shipping Methods













If you have any question about G5AK-237P-DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com