



G5CA-1A-E DC5 Information



For Reference Only

Part Number G5CA-1A-E DC5

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 15A 5V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G5CA-1A-E DC5 Specifications

Manufacturer Part Number G5CA-1A-E DC5 Manufacturer Omron Electronics Inc-EMC Div Category Relays Power Relays, Over 2 Amps Package - Series G5CA Relay Type General Purpose Coil Type Non Latching Coil Current 40mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG5CARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current40mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)15ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time10msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G5CA-1A-E DC5
Package - Series G5CA Relay Type General Purpose Coil Type Non Latching Coil Current 40mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Termination Style PC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG5CARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current40mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)15ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time10msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesG5CARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current40mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)15ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time10msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 40mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil TypeNon LatchingCoil Current40mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)15ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time10msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Series	G5CA
Coil Current40mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)15ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.5 VDCOperate Time10msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Relay Type	General Purpose
Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Current	40mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style	Coil Voltage	5VDC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style 250VAC, 125VDC - Max 3.75 VDC 10ms 10ms Position Through Hole PC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style 3.75 VDC 10ms 10ms Features PC Pin	Contact Rating (Current)	15A
Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	250VAC, 125VDC - Max
Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	3.75 VDC
Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	0.5 VDC
Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Operate Time	10ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	10ms
Termination Style PC Pin	Features	Sealed - Flux Protection
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

G5CA-1A-E DC5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G5CA-1A-E DC5 Payment Methods





















G5CA-1A-E DC5 Shipping Methods













If you have any question about G5CA-1A-E DC5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com