



G5J-1-TP-M-DC12 Information

Heisener.com

Part Number G5J-1-TP-M-DC12

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 16A 12V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G5J-1-TP-M-DC12 Specifications

Manufacturer Part Number GSJ-1-TP-M-DC12 Manufacturer Omron Electronics Inc-EMC Div Category Relays Package - Series G5J Relay Type General Purpose Coil Type Non Latching Coil Current 58.3mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG5JRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current58.3mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.187" (4.7mm)	Manufacturer Part Number	G5J-1-TP-M-DC12
Package - Series G5J Relay Type General Purpose Coil Type Non Latching Coil Current 58.3mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Manufacturer	Omron Electronics Inc-EMC Div
Package - Series G5J Relay Type General Purpose Coil Type Non Latching Coil Current 58.3mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Category	Relays
Series G5J Relay Type General Purpose Coil Type Non Latching Coil Current 58.3mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 58.3 mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 5ms Features Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7 mm)	Package	-
Coil TypeNon LatchingCoil Current58.3mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.2 VDCOperate Time20msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin, Quick Connect - 0.187" (4.7mm)	Series	G5J
Coil Current 58.3mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Relay Type	General Purpose
Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Coil Current	58.3mA
Contact Rating (Current) Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 5ms Features - Mounting Type Through Hole Termination Style 16A 250VAC, 30VDC - Max 8.4 VDC 1.2 VDC 20ms 1.2 VDC 20ms PC Pin, Quick Connect - 0.187" (4.7mm)	Coil Voltage	12VDC
Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) 1.2 VDC Operate Time 20ms Release Time 5ms Features - Mounting Type Through Hole Termination Style 8.4 VDC 1.2 VDC 20ms Through Hole PC Pin, Quick Connect - 0.187" (4.7mm)	Contact Rating (Current)	16A
Turn Off Voltage (Min) Operate Time 20ms Release Time 5ms Features - Mounting Type Through Hole Termination Style 1.2 VDC 20ms Through Hole PC Pin, Quick Connect - 0.187" (4.7mm)	Switching Voltage	250VAC, 30VDC - Max
Operate Time 20ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Turn On Voltage (Max)	8.4 VDC
Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Turn Off Voltage (Min)	1.2 VDC
Features - Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Operate Time	20ms
Mounting Type Through Hole Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Release Time	5ms
Termination Style PC Pin, Quick Connect - 0.187" (4.7mm)	Features	-
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin, Quick Connect - 0.187" (4.7mm)
		Report errors?

G5J-1-TP-M-DC12 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G5J-1-TP-M-DC12 Payment Methods





















G5J-1-TP-M-DC12 Shipping Methods













If you have any question about G5J-1-TP-M-DC12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com