

G5LB-1-DC48 Information



For Reference Only

Part Number G5LB-1-DC48

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPDT 10A 48V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G5LB-1-DC48 Specifications

Manufacturer Part Number G5LB-1-DC48 Manufacturer Omron Electronics Inc-EMC Div Category Relays Power Relays, Over 2 Amps - Series G5LB Relay Type General Purpose Coil Type Non Latching Coil Current 7.6mA Coil Voltage 48VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 10ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Rip		
CategoryRelaysPackage-SeriesG5LBRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current7.6mACoil Voltage48VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)4.8 VDCOperate Time10msRelease Time5msFeatures-Mounting TypeThrough Hole	Manufacturer Part Number	G5LB-1-DC48
Package - G5LB Relay Type General Purpose Coil Type Non Latching Coil Current 7.6mA Coil Voltage 48VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 10ms Release Time 5ms Features - Mounting Type Through Hole	Manufacturer	Omron Electronics Inc-EMC Div
Package - G5LB Relay Type General Purpose Coil Type Non Latching Coil Current 7.6mA Coil Voltage 48VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 10ms Release Time 5ms Features - Mounting Type Through Hole	Category	Relays
SeriesG5LBRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current7.6mACoil Voltage48VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)4.8 VDCOperate Time10msRelease Time5msFeatures-Mounting TypeThrough Hole		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current7.6mACoil Voltage48VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)4.8 VDCOperate Time10msRelease Time5msFeatures-Mounting TypeThrough Hole	Package	-
Coil Type Non Latching Coil Current 7.6mA Coil Voltage 48VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 10ms Release Time 5ms Features - Mounting Type Through Hole	Series	G5LB
Coil Current7.6mACoil Voltage48VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)4.8 VDCOperate Time10msRelease Time5msFeatures-Mounting TypeThrough Hole	Relay Type	General Purpose
Coil Voltage48VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)4.8 VDCOperate Time10msRelease Time5msFeatures-Mounting TypeThrough Hole	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 10ms Release Time 5ms Features - Mounting Type Through Hole	Coil Current	7.6mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 7urn Off Voltage (Min) 4.8 VDC Operate Time 10ms Release Time 5ms Features - Mounting Type Through Hole	Coil Voltage	48VDC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 10ms Release Time 5ms Features - Mounting Type Through Hole	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 10ms Release Time 5ms Features - Mounting Type Through Hole	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 10ms Release Time 5ms Features - Mounting Type Through Hole	Switching Voltage	250VAC, 125VDC - Max
Operate Time 10ms Release Time 5ms Features - Mounting Type Through Hole	Turn On Voltage (Max)	36 VDC
Release Time 5ms Features - Mounting Type Through Hole	Turn Off Voltage (Min)	4.8 VDC
Features - Mounting Type Through Hole	Operate Time	10ms
Mounting Type Through Hole	Release Time	5ms
	Features	-
Termination Style DC Pin	Mounting Type	Through Hole
remination style	Termination Style	PC Pin
Report errors?		Report errors?

G5LB-1-DC48 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G5LB-1-DC48 Payment Methods



















G5LB-1-DC48 Shipping Methods













If you have any question about G5LB-1-DC48, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com