

G5LE-1 DC6 Information



For Reference Only

Part Number G5LE-1 DC6

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPDT 10A 6V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G5LE-1 DC6 Specifications

Manufacturer Part Number G5LE-1 DC6 Manufacturer Omron Electronics Inc-EMC Div Category Relays Power Relays, Over 2 Amps Package - Series G5LE Relay Type General Purpose Coil Type Non Latching Coil Current 66.7mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG5LERelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current66.7mACoil Voltage6VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.6 VDCOperate Time10msRelease Time5msFeaturesInsulation - Class B, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G5LE-1 DC6
Package - Series G5LE Relay Type General Purpose Coil Type Non Latching Coil Current 66.7mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style	Manufacturer	Omron Electronics Inc-EMC Div
Package - GSLE Relay Type General Purpose Coil Type Non Latching Coil Current 66.7 mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 5 ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Category	Relays
Series G5LE Relay Type General Purpose Coil Type Non Latching Coil Current 66.7mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 66.7mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil Type Non Latching Coil Current 66.7mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Series	G5LE
Coil Current Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style 66.7mA 66.7m	Relay Type	General Purpose
Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Current	66.7mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style	Coil Voltage	6VDC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 10ms Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	250VAC, 125VDC - Max
Operate Time 10ms Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	4.2 VDC
Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	0.6 VDC
Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Operate Time	10ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	Insulation - Class B, Sealed - Flux Protection
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

G5LE-1 DC6 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G5LE-1 DC6 Payment Methods



















G5LE-1 DC6 Shipping Methods













If you have any question about G5LE-1 DC6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com