



### **G5LE-14-ASI DC6 Information**



For Reference Only

Part Number G5LE-14-ASI DC6

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPDT 10A 6V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **G5LE-14-ASI DC6 Specifications**

Manufacturer Part Number         G5LE-14-ASI DC6           Manufacturer         Omron Electronics Inc-EMC Div           Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         G5LE           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         66.7mA           Coil Voltage         6VDC           Contact Form         SPDT (1 Form C)           Contact Rating (Current)         10A           Switching Voltage         250VAC, 125VDC - Max           Turn On Voltage (Max)         4.5 VDC           Turn Off Voltage (Min)         0.6 VDC           Operate Time         10ms           Release Time         5ms           Features         Insulation - Class B, Sealed - Fully           Mounting Type         Through Hole           Termination Style         PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG5LERelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current66.7mACoil Voltage6VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)4.5 VDCTurn Off Voltage (Min)0.6 VDCOperate Time10msRelease Time5msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G5LE-14-ASI DC6
Package Series G5LE Relay Type General Purpose Coil Type Non Latching Coil Current 66.7mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class B, Sealed - Fully Mounting Type Termination Style Prime SELE  Features Features Turn On Voltage (Min) Turn Off Hole Termination Style	Manufacturer	Omron Electronics Inc-EMC Div
Package         -           Series         G5LE           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         66.7mA           Coil Voltage         6VDC           Contact Form         SPDT (1 Form C)           Contact Rating (Current)         10A           Switching Voltage         250VAC, 125VDC - Max           Turn On Voltage (Max)         4.5 VDC           Turn Off Voltage (Min)         0.6 VDC           Operate Time         10ms           Release Time         5ms           Features         Insulation - Class B, Sealed - Fully           Mounting Type         Through Hole           Termination Style         PC Pin	Category	Relays
SeriesG5LERelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current66.7mACoil Voltage6VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)4.5 VDCTurn Off Voltage (Min)0.6 VDCOperate Time10msRelease Time5msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current66.7mACoil Voltage6VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)4.5 VDCTurn Off Voltage (Min)0.6 VDCOperate Time10msRelease Time5msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current66.7mACoil Voltage6VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)4.5 VDCTurn Off Voltage (Min)0.6 VDCOperate Time10msRelease Time5msFeaturesInsulation - Class B, Sealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Series	G5LE
Coil Current Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 4.5 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPDT (1 Form C)  Contact Rating (Current)  Switching Voltage  250VAC, 125VDC - Max  Turn On Voltage (Max)  4.5 VDC  Turn Off Voltage (Min)  Operate Time  10ms  Release Time  5ms  Features  Insulation - Class B, Sealed - Fully  Mounting Type  Through Hole  Termination Style	Coil Current	66.7mA
Contact Rating (Current)  Switching Voltage  250VAC, 125VDC - Max  Turn On Voltage (Max)  4.5 VDC  Turn Off Voltage (Min)  0.6 VDC  Operate Time  10ms  Release Time  5ms  Features  Insulation - Class B, Sealed - Fully  Mounting Type  Through Hole  Termination Style	Coil Voltage	6VDC
Switching Voltage  250VAC, 125VDC - Max  Turn On Voltage (Max)  4.5 VDC  Turn Off Voltage (Min)  0.6 VDC  Operate Time  10ms  Release Time  5ms  Features  Insulation - Class B, Sealed - Fully  Mounting Type  Through Hole  Termination Style  PC Pin	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max)  4.5 VDC  Turn Off Voltage (Min)  0.6 VDC  Operate Time  10ms  Release Time  5ms  Features  Insulation - Class B, Sealed - Fully  Mounting Type  Through Hole  Termination Style  PC Pin	Contact Rating (Current)	10A
Turn Off Voltage (Min)  Operate Time  10ms  Release Time  5ms  Features  Insulation - Class B, Sealed - Fully  Mounting Type  Through Hole  Termination Style  PC Pin	Switching Voltage	250VAC, 125VDC - Max
Operate Time 10ms Release Time 5ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	4.5 VDC
Release Time 5ms Features Insulation - Class B, Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	0.6 VDC
Features Insulation - Class B, Sealed - Fully  Mounting Type Through Hole  Termination Style PC Pin	Operate Time	10ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	Insulation - Class B, Sealed - Fully
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

#### **G5LE-14-ASI DC6 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **G5LE-14-ASI DC6 Payment Methods**



















### **G5LE-14-ASI DC6 Shipping Methods**













If you have any question about G5LE-14-ASI DC6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com