



#### **G5LE-1A-ACD-DC12 Information**



For Reference Only

Part Number G5LE-1A-ACD-DC12

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPST 10A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **G5LE-1A-ACD-DC12 Specifications**

Manufacturer Part Number       G5LE-1A-ACD-DC12         Manufacturer       Omron Electronics Inc-EMC Div         Category       Relays         Power Relays, Over 2 Amps         Package       -         Series       G5LE         Relay Type       General Purpose         Coil Type       Non Latching         Coil Current       33.3mA         Coil Voltage       12VDC         Contact Form       SPST-NO (1 Form A)         Contact Rating (Current)       10A         Switching Voltage       250VAC, 125VDC - Max         Turn On Voltage (Max)       9 VDC         Turn Off Voltage (Min)       1.2 VDC         Operate Time       10ms         Release Time       5ms         Features       Insulation - Class B, Sealed - Flux Protection         Mounting Type       Through Hole         Termination Style       PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG5LERelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time5msFeaturesInsulation - Class B, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G5LE-1A-ACD-DC12
Package-SeriesG5LERelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time5msFeaturesInsulation - Class B, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG5LERelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time5msFeaturesInsulation - Class B, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesG5LERelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current33.3mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time5msFeaturesInsulation - Class B, Sealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil Type Non Latching Coil Current 33.3mA  Coil Voltage 12VDC  Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 10A  Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 9 VDC  Turn Off Voltage (Min) 1.2 VDC  Operate Time 10ms  Release Time 5ms  Features Insulation - Class B, Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Series	G5LE
Coil Current 33.3mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 12VDC  Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 10A  Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 9 VDC  Turn Off Voltage (Min) 1.2 VDC  Operate Time 10ms  Release Time 5ms  Features Insulation - Class B, Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 10A  Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 9 VDC  Turn Off Voltage (Min) 1.2 VDC  Operate Time 10ms  Release Time 5ms  Features Insulation - Class B, Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Coil Current	33.3mA
Contact Rating (Current)  Switching Voltage  250VAC, 125VDC - Max  Turn On Voltage (Max)  9 VDC  Turn Off Voltage (Min)  1.2 VDC  Operate Time  10ms  Release Time  5ms  Features  Insulation - Class B, Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Coil Voltage	12VDC
Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 9 VDC  Turn Off Voltage (Min) 1.2 VDC  Operate Time 10ms  Release Time 5ms  Features Insulation - Class B, Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max)  9 VDC  Turn Off Voltage (Min)  1.2 VDC  Operate Time  10ms  Release Time  5ms  Features  Insulation - Class B, Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Contact Rating (Current)	10A
Turn Off Voltage (Min)  1.2 VDC  Operate Time  10ms  Release Time  5ms  Features  Insulation - Class B, Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Switching Voltage	250VAC, 125VDC - Max
Operate Time 10ms Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	9 VDC
Release Time 5ms Features Insulation - Class B, Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	1.2 VDC
Features Insulation - Class B, Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Operate Time	10ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	Insulation - Class B, Sealed - Flux Protection
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

#### **G5LE-1A-ACD-DC12 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **G5LE-1A-ACD-DC12** Payment Methods





















### **G5LE-1A-ACD-DC12** Shipping Methods













If you have any question about G5LE-1A-ACD-DC12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com