



G5NB-1A4 DC24 Information



For Reference Only

Part Number G5NB-1A4 DC24

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 3A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G5NB-1A4 DC24 Specifications

Manufacturer Part Number G5NB-1A4 DC24 Manufacturer Omron Electronics Inc-EMC Div Category Relays Power Relays, Over 2 Amps Package - Series G5NB Relay Type General Purpose Coil Type Non Latching Coil Current 8.3mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 3A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 10ms Features Sealed - Fully Mounting Type Through Hole		
CategoryRelaysPackage-SeriesG5NBRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.3mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)3ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time10msRelease Time10msFeaturesSealed - Fully	Manufacturer Part Number	G5NB-1A4 DC24
Package - Series G5NB Relay Type General Purpose Coil Type Non Latching Coil Current 8.3mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 3A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 10ms Features Sealed - Fully	Manufacturer	Omron Electronics Inc-EMC Div
Package - G5NB Relay Type General Purpose Coil Type Non Latching Coil Current 8.3mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 3A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 10ms Features Sealed - Fully	Category	Relays
Series G5NB Relay Type General Purpose Coil Type Non Latching Coil Current 8.3mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 3A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 10ms Features Sealed - Fully		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 8.3mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 3A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 10ms Features Sealed - Fully	Package	-
Coil Type Non Latching Coil Current 8.3mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 3A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 10ms Features Sealed - Fully	Series	G5NB
Coil Current8.3mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)3ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time10msRelease Time10msFeaturesSealed - Fully	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 3A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 10ms Features Sealed - Fully	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 3A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 10ms Features Sealed - Fully	Coil Current	8.3mA
Contact Rating (Current) Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 10ms Features Sealed - Fully	Coil Voltage	24VDC
Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 10ms Features Sealed - Fully	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 10ms Features Sealed - Fully	Contact Rating (Current)	3A
Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms Features Sealed - Fully	Switching Voltage	250VAC, 30VDC - Max
Operate Time 10ms Release Time 10ms Features Sealed - Fully	Turn On Voltage (Max)	18 VDC
Release Time 10ms Features Sealed - Fully	Turn Off Voltage (Min)	2.4 VDC
Features Sealed - Fully	Operate Time	10ms
·	Release Time	10ms
Mounting Type Through Hole	Features	Sealed - Fully
	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

G5NB-1A4 DC24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G5NB-1A4 DC24 Payment Methods



















G5NB-1A4 DC24 Shipping Methods













If you have any question about G5NB-1A4 DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com