

## **G5NB-1A4-EL-HA DC12**

#### G5NB-1A4-EL-HA DC12 Information



For Reference Only

Part Number G5NB-1A4-EL-HA DC12

Manufacturer Omron Electronics Inc-EMC Div

**Category** Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPST 7A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# G5NB-1A4-EL-HA DC12 Specifications

Manufacturer Part NumberG5NB-1A4-EL-HA DC12ManufacturerOmron Electronics Inc-EMC DivCategoryRelaysPackage-SeriesG5NB-ELRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current16.7mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)7ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time10msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPackage-SeriesG5NB-ELRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current16.7mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)7ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time10msFeaturesSealed - FullyMounting TypeThrough Hole	Manufacturer Part Number	G5NB-1A4-EL-HA DC12
Package         -           Series         G5NB-EL           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         16.7mA           Coil Voltage         12VDC           Contact Form         SPST-NO (1 Form A)           Contact Rating (Current)         7A           Switching Voltage         250VAC, 30VDC - Max           Turn On Voltage (Max)         9 VDC           Turn Off Voltage (Min)         1.2 VDC           Operate Time         10ms           Release Time         10ms           Features         Sealed - Fully           Mounting Type         Through Hole	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG5NB-ELRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current16.7mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)7ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time10msFeaturesSealed - FullyMounting TypeThrough Hole	Category	Relays
SeriesG5NB-ELRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current16.7mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)7ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1.2 VDCOperate Time10msRelease Time10msFeaturesSealed - FullyMounting TypeThrough Hole		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 16.7mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 7A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 10ms Features Sealed - Fully Mounting Type Through Hole	Package	-
Coil Type Non Latching Coil Current 16.7mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 7A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 10ms Features Sealed - Fully Mounting Type Through Hole	Series	G5NB-EL
Coil Current 16.7mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 7A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 10ms Release Time 10ms Features Sealed - Fully Mounting Type Through Hole	Relay Type	General Purpose
Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 7A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 10ms Release Time 10ms Features Sealed - Fully Mounting Type Through Hole	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A)  Contact Rating (Current)  Switching Voltage  250VAC, 30VDC - Max  Turn On Voltage (Max)  9 VDC  Turn Off Voltage (Min)  1.2 VDC  Operate Time  10ms  Release Time  10ms  Features  Sealed - Fully  Mounting Type  Through Hole	Coil Current	16.7mA
Contact Rating (Current)  Switching Voltage  250VAC, 30VDC - Max  Turn On Voltage (Max)  9 VDC  Turn Off Voltage (Min)  1.2 VDC  Operate Time  10ms  Release Time  10ms  Features  Sealed - Fully  Mounting Type  Through Hole	Coil Voltage	12VDC
Switching Voltage 250VAC, 30VDC - Max  Turn On Voltage (Max) 9 VDC  Turn Off Voltage (Min) 1.2 VDC  Operate Time 10ms  Release Time 10ms  Features Sealed - Fully  Mounting Type Through Hole	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max)  7 Turn Off Voltage (Min)  9 VDC  1.2 VDC  Operate Time  10ms  Release Time  10ms  Features  Sealed - Fully  Mounting Type  Through Hole	Contact Rating (Current)	7A
Turn Off Voltage (Min)  Operate Time  10ms  Release Time  10ms  Features  Sealed - Fully  Mounting Type  Through Hole	Switching Voltage	250VAC, 30VDC - Max
Operate Time10msRelease Time10msFeaturesSealed - FullyMounting TypeThrough Hole	Turn On Voltage (Max)	9 VDC
Release Time 10ms Features Sealed - Fully Mounting Type Through Hole	Turn Off Voltage (Min)	1.2 VDC
Features Sealed - Fully Mounting Type Through Hole	Operate Time	10ms
Mounting Type Through Hole	Release Time	10ms
	Features	Sealed - Fully
Termination Style PC Pin	Mounting Type	Through Hole
	Termination Style	PC Pin
Report errors?		Report errors?

#### **G5NB-1A4-EL-HA DC12 Guarantees**



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **G5NB-1A4-EL-HA DC12 Payment Methods**



















## G5NB-1A4-EL-HA DC12 Shipping Methods













If you have any question about G5NB-1A4-EL-HA DC12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com