

G5NB-1A4-EL-HA DC24

G5NB-1A4-EL-HA DC24 Information



For Reference Only

Part Number G5NB-1A4-EL-HA DC24

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 7A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G5NB-1A4-EL-HA DC24 Specifications

Manufacturer Part Number G5NB-1A4-EL-HA DC24 Manufacturer Omron Electronics Inc-EMC Div Category Relays Power Relays, Over 2 Amps Package - Series G5NB-EL Relay Type General Purpose Coil Type Non Latching Coil Current 8.3mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 7A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 10ms Features Sealed - Fully		
Category Relays Power Relays, Over 2 Amps - Series G5NB-EL Relay Type General Purpose Coil Type Non Latching Coil Current 8.3mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 7A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) Qerate Time 10ms Release Time	Manufacturer Part Number	G5NB-1A4-EL-HA DC24
Package - Series G5NB-EL Relay Type General Purpose Coil Type Non Latching Coil Current 8.3mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 7A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 10ms	Manufacturer	Omron Electronics Inc-EMC Div
Package - G5NB-EL Relay Type General Purpose Coil Type Non Latching Coil Current 8.3mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 7A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 10ms	Category	Relays
Series G5NB-EL Relay Type General Purpose Coil Type Non Latching Coil Current 8.3mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 7A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 10ms		Power Relays, Over 2 Amps
Relay Type Coil Type Non Latching Coil Current 8.3mA Coil Voltage Contact Form SPST-NO (1 Form A) Contact Rating (Current) 7A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms	Package	-
Coil Type Non Latching Coil Current 8.3mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 7A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 10ms	Series	G5NB-EL
Coil Current8.3mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)7ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)18 VDCTurn Off Voltage (Min)2.4 VDCOperate Time10msRelease Time10ms	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 7A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 10ms	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 7A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 10ms	Coil Current	8.3mA
Contact Rating (Current) Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 10ms	Coil Voltage	24VDC
Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 18 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 10ms Release Time 10ms	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms	Contact Rating (Current)	7A
Turn Off Voltage (Min) Operate Time 10ms Release Time 10ms	Switching Voltage	250VAC, 30VDC - Max
Operate Time 10ms Release Time 10ms	Turn On Voltage (Max)	18 VDC
Release Time 10ms	Turn Off Voltage (Min)	2.4 VDC
	Operate Time	10ms
Features Sealed - Fully	Release Time	10ms
	Features	Sealed - Fully
Mounting Type Through Hole	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

G5NB-1A4-EL-HA DC24 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G5NB-1A4-EL-HA DC24 Payment Methods





















G5NB-1A4-EL-HA DC24 Shipping Methods













If you have any question about G5NB-1A4-EL-HA DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com