



G5PA-1DC12(PF) Information

Heisener.com

Part Number G5PA-1DC12(PF)

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 5A 12V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G5PA-1DC12(PF) Specifications

Manufacturer Part NumberG5PA-1DC12(PF)ManufacturerOmron Electronics Inc-EMC DivCategoryRelaysPackage-SeriesG5PA-1Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current20.8mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)5ASwitching Voltage277VAC, 30VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG5PA-1Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current20.8mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)5ASwitching Voltage277VAC, 30VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G5PA-1DC12(PF)
Package - G5PA-1 Relay Type General Purpose Coil Type Non Latching Coil Current 20.8mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Trimous SPST-NO (1 Form A) Trough Hole Termination Style PC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG5PA-1Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current20.8mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)5ASwitching Voltage277VAC, 30VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
Series G5PA-1 Relay Type General Purpose Coil Type Non Latching Coil Current 20.8mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 20.8mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil TypeNon LatchingCoil Current20.8mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)5ASwitching Voltage277VAC, 30VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Series	G5PA-1
Coil Current 20.8mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 5ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 5ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Current	20.8mA
Contact Rating (Current) Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style	Coil Voltage	12VDC
Switching Voltage 277VAC, 30VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) 7 Turn Off Voltage (Min) 9.6 VDC 1.2 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	277VAC, 30VDC - Max
Operate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	9.6 VDC
Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	1.2 VDC
Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Operate Time	15ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	Sealed - Flux Protection
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
*		Report errors?

G5PA-1DC12(PF) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G5PA-1DC12(PF) Payment Methods



















G5PA-1DC12(PF) Shipping Methods













If you have any question about G5PA-1DC12(PF), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com