

G5RL-1A-E-TV8 DC5

G5RL-1A-E-TV8 DC5 Information

Part Number G5RL-1A-E-TV8 DC5

Manufacturer Omron Electronics Inc-EMC Div

Category

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 16A 5V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G5RL-1A-E-TV8 DC5 Specifications

Manufacturer Part NumberG5RL-1A-E-TV8 DC5ManufacturerOmron Electronics Inc-EMC DivCategoryRelaysPackage-SeriesG5RLRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current80mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage250VAC, 24VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.5 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough Hole		
CategoryRelaysPackage-SeriesG5RLRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current80mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage250VAC, 24VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.5 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux Protection	Manufacturer Part Number	G5RL-1A-E-TV8 DC5
Package - Series G5RL Relay Type General Purpose Coil Type Non Latching Coil Current 80mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC, 24VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection	Manufacturer	Omron Electronics Inc-EMC Div
Package - G5RL Relay Type General Purpose Coil Type Non Latching Coil Current 80mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC, 24VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection	Category	Relays
SeriesG5RLRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current80mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage250VAC, 24VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.5 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux Protection		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 80mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC, 24VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection	Package	-
Coil Type Non Latching Coil Current 80mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC, 24VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection	Series	G5RL
Coil Current80mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage250VAC, 24VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.5 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux Protection	Relay Type	General Purpose
Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 250VAC, 24VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) Switching Voltage 250VAC, 24VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection	Coil Current	80mA
Contact Rating (Current) Switching Voltage 250VAC, 24VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection	Coil Voltage	5VDC
Switching Voltage 250VAC, 24VDC - Max Turn On Voltage (Max) 3.5 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection	Contact Rating (Current)	16A
Turn Off Voltage (Min) Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection	Switching Voltage	250VAC, 24VDC - Max
Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection	Turn On Voltage (Max)	3.5 VDC
Release Time 5ms Features Sealed - Flux Protection	Turn Off Voltage (Min)	0.5 VDC
Features Sealed - Flux Protection	Operate Time	15ms
	Release Time	5ms
Mounting Type Through Hole	Features	Sealed - Flux Protection
	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

G5RL-1A-E-TV8 DC5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G5RL-1A-E-TV8 DC5 Payment Methods



















G5RL-1A-E-TV8 DC5 Shipping Methods













If you have any question about G5RL-1A-E-TV8 DC5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com