



G5RL-U1-E-DC12 Information



For Reference Only

Part Number G5RL-U1-E-DC12

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY PWR LATCH SPDT 16A 12VDC

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G5RL-U1-E-DC12 Specifications

Manufacturer Part Number G5RL-U1-E-DC12 Manufacturer Omron Electronics Inc-EMC Div Category Relays Power Relays, Over 2 Amps Package - Series G5RL-U Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 50mA Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 16A Switching Voltage 250VAC, 24VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 15ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG5RL-URelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current50mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)16ASwitching Voltage250VAC, 24VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time15msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G5RL-U1-E-DC12
Package-SeriesG5RL-URelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current50mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)16ASwitching Voltage250VAC, 24VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time15msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG5RL-URelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current50mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)16ASwitching Voltage250VAC, 24VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time15msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesG5RL-URelay TypeGeneral PurposeCoil TypeLatching, Single CoilCoil Current50mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)16ASwitching Voltage250VAC, 24VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time15msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Latching, Single Coil Coil Current 50mA Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 16A Switching Voltage 250VAC, 24VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 15ms Release Time 15ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil Type Latching, Single Coil Coil Current 50mA Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 16A Switching Voltage 250VAC, 24VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 15ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Series	G5RL-U
Coil Current50mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)16ASwitching Voltage250VAC, 24VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time15msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Relay Type	General Purpose
Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 16A Switching Voltage 250VAC, 24VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 15ms Release Time 5eatures Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Type	Latching, Single Coil
Contact Form SPDT (1 Form C) Contact Rating (Current) 16A Switching Voltage 250VAC, 24VDC - Max Turn On Voltage (Max) 7urn Off Voltage (Min) Operate Time 15ms Release Time 15ms Release Time 15ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Current	50mA
Contact Rating (Current) Switching Voltage 250VAC, 24VDC - Max Turn On Voltage (Max) 8.4 VDC Turn Off Voltage (Min) Operate Time 15ms Release Time 15ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style	Coil Voltage	12VDC
Switching Voltage Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 15ms Release Time 15ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style 250VAC, 24VDC - Max 8.4 VDC	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 15ms Release Time 15ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style 8.4 VDC	Contact Rating (Current)	16A
Turn Off Voltage (Min) Operate Time 15ms Release Time 15ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	250VAC, 24VDC - Max
Operate Time 15ms Release Time 15ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	8.4 VDC
Release Time 15ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	-
Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Operate Time	15ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	15ms
Termination Style PC Pin	Features	Sealed - Flux Protection
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
· · · · · · · · · · · · · · · · · · ·		Report errors?

G5RL-U1-E-DC12 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G5RL-U1-E-DC12 Payment Methods



















G5RL-U1-E-DC12 Shipping Methods













If you have any question about G5RL-U1-E-DC12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com