

G5SB-14 DC9 Information



For Reference Only

Part Number G5SB-14 DC9

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GENERAL PURPOSE SPDT 5A 9V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G5SB-14 DC9 Specifications

Manufacturer Part Number G5SB-14 DC9 Manufacturer Omron Electronics Inc-EMC Div Category Relays Power Relays, Over 2 Amps Package - Series G5SB Relay Type General Purpose Coil Type Non Latching Coil Current 44.4mA Coil Voltage 9VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) 0.45 VDC Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG5SBRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current44.4mACoil Voltage9VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)0.45 VDCOperate Time10msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G5SB-14 DC9
Package - Series G5SB Relay Type General Purpose Coil Type Non Latching Coil Current 44.4mA Coil Voltage 9VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) 0.45 VDC Operate Time 10ms Release Time Features Sealed - Fully Mounting Type Through Hole Termination Style	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG5SBRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current44.4mACoil Voltage9VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)0.45 VDCOperate Time10msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
Series G5SB Relay Type General Purpose Coil Type Non Latching Coil Current 44.4mA Coil Voltage 9VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) 0.45 VDC Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin		Power Relays, Over 2 Amps
Relay Type Coil Type Non Latching Coil Current 44.4mA Coil Voltage 9VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) 0.45 VDC Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil TypeNon LatchingCoil Current44.4mACoil Voltage9VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)0.45 VDCOperate Time10msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Series	G5SB
Coil Current 44.4mA Coil Voltage 9VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) 0.45 VDC Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 9VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) 0.45 VDC Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) 0.45 VDC Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Coil Current	44.4mA
Contact Rating (Current) Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) 0.45 VDC Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style	Coil Voltage	9VDC
Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) 0.45 VDC Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style 6.75 VDC 0.45 VDC 0.45 VDC 10ms Formination Style	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	250VAC, 30VDC - Max
Operate Time 10ms Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	6.75 VDC
Release Time 5ms Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	0.45 VDC
Features Sealed - Fully Mounting Type Through Hole Termination Style PC Pin	Operate Time	10ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	Sealed - Fully
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
•		Report errors?

G5SB-14 DC9 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G5SB-14 DC9 Payment Methods



















G5SB-14 DC9 Shipping Methods













If you have any question about G5SB-14 DC9, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com