



G5SB-1A4 DC12 Information



For Reference Only

Part Number G5SB-1A4 DC12

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 5A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G5SB-1A4 DC12 Specifications

Manufacturer Part Number G5SB-1A4 DC12 Manufacturer Omron Electronics Inc-EMC Div Category Relays Power Relays, Over 2 Amps Package - Series G5SB Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms Release Time 5ms		
Category Relays Power Relays, Over 2 Amps Package - Series G5SB Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Relays Power Relays, Over 2 Amps Power Relays,	Manufacturer Part Number	G5SB-1A4 DC12
Package - Series G5SB Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms	Manufacturer	Omron Electronics Inc-EMC Div
Package - G5SB Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 1000000000000000000000000000000000000	Category	Relays
Series G5SB Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 33.3mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms	Package	-
Coil Type Non Latching Coil Current 33.3mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms	Series	G5SB
Coil Current 33.3mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms	Relay Type	General Purpose
Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 5A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms	Coil Current	33.3mA
Contact Rating (Current) Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms	Coil Voltage	12VDC
Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 0.6 VDC Operate Time 10ms	Contact Rating (Current)	5A
Turn Off Voltage (Min) Operate Time 0.6 VDC 10ms	Switching Voltage	250VAC, 30VDC - Max
Operate Time 10ms	Turn On Voltage (Max)	9 VDC
•	Turn Off Voltage (Min)	0.6 VDC
Release Time 5ms	Operate Time	10ms
	Release Time	5ms
Features Sealed - Fully	Features	Sealed - Fully
Mounting Type Through Hole	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

G5SB-1A4 DC12 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G5SB-1A4 DC12 Payment Methods



















G5SB-1A4 DC12 Shipping Methods













If you have any question about G5SB-1A4 DC12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com