

G5V-2-H1 DC48

G5V-2-H1 DC48 Information



Part Number	G5V-2-H1 DC48	
Manufacturer	Omron Electronics Inc-EMC Div	
Category	Relays Signal Relays, Up to 2 Amps	
Description	RELAY GEN PURPOSE DPDT 1A 48V	
Package	-	
	For the pricing/inventory/lead time, please contact	
	us	
Website: https://www.heisener.com		
	E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



G5V-2-H1 DC48 Specifications

ManufacturerOmron Electronics Inc-EMC DivCategoryRelaysPackageSignal Relays, Up to 2 AmpsPackage-StriesG5V-2Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current6.25mACoil AutopeHaVDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 125VDC - MaxTurn On Voltage (Max)64 VDCCurrent Gimmer36 VDCSwitching Voltage (Max)36 VDCStries3msRelease TimeSinel FullyFeaturesKnouting Type		
CategoryRelaysPackage-Package-SeriesG5V-2Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current6.25mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 125VDC - MaxTurn On Voltage (Max)36 VDCQuerta Time36 VDCSeries Time3msRelease TimeSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G5V-2-H1 DC48
Signal Relays, Up to 2 AmpsPackage-SeriesG5V-2Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current6.25mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 125VDC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)2.4 VDCOperate Time3msRelease TimeSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG5V-2Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current6.25mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 125VDC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)2.4 VDCOperate Time7msRelease TimeSailed - FullyMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesG5V-2Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current6.25mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 125VDC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)2.4 VDCOperate Time7msRelease TimeSealed - FullyFeaturesSealed - FullyMounting TypePC Pin		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current6.25mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage36 VDC - MaxTurn On Voltage (Max)2.4 VDCOperate Time7msRelease TimeSealed - FullyFeaturesSealed - FullyMounting TypePC Pin	Package	-
Coil TypeNon LatchingCoil Current6.25mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 125VDC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)2.4 VDCOperate Time7msRelease TimeSmaleFeaturesScaled - FullyMounting TypeThrough HoleTermination StylePC Pin	Series	G5V-2
Coil Current6.25mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 125VDC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)2.4 VDCOperate Time7msRelease Time3msFeaturesSealed - FullyMounting TypeThrough HolePC PinPC Pin	Relay Type	General Purpose
Coil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 125VDC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)2.4 VDCOperate Time7msRelease TimesSaled - FullyFeaturesSnog HoleMounting TypeThrough HoleTermination StylePC Pin	Coil Type	Non Latching
Contact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 125VDC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)2.4 VDCOperate Time7msRelease Time3msFeaturesSealed - FullyMounting TypeThrough HolePC PinPC Pin	Coil Current	6.25mA
Contact Rating (Current)1ASwitching Voltage125VAC, 125VDC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)2.4 VDCOperate Time7msRelease Time3msFeaturesSealed - FullyMounting TypeThrough HolePermination StylePC Pin	Coil Voltage	48VDC
Switching Voltage125VAC, 125VDC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)2.4 VDCOperate Time7msRelease Time3msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)36 VDCTurn Off Voltage (Min)2.4 VDCOperate Time7msRelease Time3msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Contact Rating (Current)	1A
Turn Off Voltage (Min)2.4 VDCOperate Time7msRelease Time3msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Switching Voltage	125VAC, 125VDC - Max
Operate Time7msRelease Time3msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	36 VDC
Release Time3msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Turn Off Voltage (Min)	2.4 VDC
FeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Operate Time	7ms
Mounting TypeThrough HoleTermination StylePC Pin	Release Time	3ms
Termination Style PC Pin	Features	Sealed - Fully
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

G5V-2-H1 DC48 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

G5V-2-H1 DC48 Payment Methods



G5V-2-H1 DC48 Shipping Methods



If you have any question about G5V-2-H1 DC48, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com