

G6A-2-L-DC24 Information



For Reference Only

Part Number G6A-2-L-DC24

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GENERAL PURPOSE DPDT 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G6A-2-L-DC24 Specifications

Manufacturer Part Number Manufacturer Omron Electronics Inc-EMC Div Relays Signal Relays, Up to 2 Amps Package - Series G6A Relay Type General Purpose Coil Current - Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) - Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time Features Mounting Type Through Hole Termination Style Omron Electronics Inc-EMC Div Release Time PC Pin Report errors?		
CategoryRelaysPackage-SeriesG6ARelay TypeGeneral PurposeCoil Type-Coil Current-Coil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)-Switching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G6A-2-L-DC24
Package - G6A Relay Type General Purpose Coil Type - Coil Current - Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) - Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Coperate Time - Release Time - Features - Mounting Type Through Hole Termination Style PC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package - Series G6A Relay Type General Purpose Coil Type - Coil Current - Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) - Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Through Hole Termination Style PC Pin	Category	Relays
SeriesG6ARelay TypeGeneral PurposeCoil Type-Coil Current-Coil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)-Switching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)-Turn Off Voltage (Min)-Operate Time-Release Time-Features-Mounting TypeThrough HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay Type Coil Type - Coil Current - Coil Voltage Contact Form DPDT (2 Form C) Contact Rating (Current) - Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) Operate Time Release Time - Release Time - Features Mounting Type Through Hole Termination Style General Purpose General Purpose General Purpose General Purpose General Purpose General Purpose General Purpose General Purpose General Purpose	Package	-
Coil Type - Coil Current - Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) - Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Through Hole Termination Style PC Pin	Series	G6A
Coil Current Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) Operate Time Release Time - Release Time Features - Mounting Type Through Hole Termination Style - POPDT (2 Form C)	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) - Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Through Hole Termination Style PC Pin	Coil Type	-
Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time - Release Time Features Mounting Type Through Hole Termination Style	Coil Current	-
Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) Operate Time Release Time - Release Time Features Mounting Type Through Hole Termination Style - Contact Rating (Current) - Turn Off Voltage (Max) - Turn Off Voltage (Min) - Tur	Coil Voltage	24VDC
Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) - Turn Off Voltage (Min) - Operate Time - Release Time - Features - Mounting Type Through Hole Termination Style PC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time - Retures Mounting Type Through Hole Termination Style - Contact Time Termination Style - Contact Time Contact Ti	Contact Rating (Current)	-
Turn Off Voltage (Min) Operate Time - Release Time - Features - Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	250VAC, 220VDC - Max
Operate Time - Release Time	Turn On Voltage (Max)	-
Release Time - Features - Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	-
Features - Mounting Type Through Hole PC Pin	Operate Time	-
Mounting Type Through Hole Termination Style PC Pin	Release Time	-
Termination Style PC Pin	Features	-
-	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

G6A-2-L-DC24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G6A-2-L-DC24 Payment Methods



















G6A-2-L-DC24 Shipping Methods













If you have any question about G6A-2-L-DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com