

## G6A-434P-ST20-US-DC24

### G6A-434P-ST20-US-DC24 Information



Part Number G6A-434P-ST20-US-DC24

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Signal Relays, Up to 2 Amps

**Description** RELAY GEN PURPOSE 4PDT 1A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **G6A-434P-ST20-US-DC24 Specifications**

Manufacturer Part Number  Manufacturer  Omron Electronics Inc-EMC Div  Relays Signal Relays, Up to 2 Amps  Package  Series  G6A  Relay Type General Purpose Coil Type Non Latching Coil Current 8.3mA Coil Voltage 24VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 1A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) Operate Time Release Time Features  Mounting Type Through Hole Termination Style  PC Pin  Report errors?		
CategoryRelaysPackage-SeriesG6ARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.3mACoil Voltage24VDCContact Form4PDT (4 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)2.4 VDCOperate Time7msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G6A-434P-ST20-US-DC24
Package-SeriesG6ARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.3mACoil Voltage24VDCContact Form4PDT (4 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)2.4 VDCOperate Time7msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package         -           Series         G6A           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         8.3mA           Coil Voltage         24VDC           Contact Form         4PDT (4 Form C)           Contact Rating (Current)         1A           Switching Voltage         250VAC, 220VDC - Max           Turn On Voltage (Max)         16.8 VDC           Turn Off Voltage (Min)         2.4 VDC           Operate Time         7ms           Release Time         5ms           Features         -           Mounting Type         Through Hole           Termination Style         PC Pin	Category	Relays
Series         G6A           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         8.3mA           Coil Voltage         24VDC           Contact Form         4PDT (4 Form C)           Contact Rating (Current)         1A           Switching Voltage         250VAC, 220VDC - Max           Turn On Voltage (Max)         16.8 VDC           Turn Off Voltage (Min)         2.4 VDC           Operate Time         7ms           Release Time         5ms           Features         -           Mounting Type         Through Hole           Termination Style         PC Pin		Signal Relays, Up to 2 Amps
Relay Type General Purpose Non Latching Coil Type Non Latching Coil Current 8.3mA Coil Voltage 24VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 1A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 7ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil Type Non Latching Coil Current 8.3mA  Coil Voltage 24VDC  Contact Form 4PDT (4 Form C)  Contact Rating (Current) 1A  Switching Voltage 250VAC, 220VDC - Max  Turn On Voltage (Max) 16.8 VDC  Turn Off Voltage (Min) 2.4 VDC  Operate Time 7ms  Release Time 5ms  Features -  Mounting Type Through Hole  Termination Style PC Pin	Series	G6A
Coil Current Coil Voltage 24VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 1A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 7ms Release Time 5ms Features - Mounting Type Through Hole Termination Style  8.3mA 8.3mA 8.3mA 24VDC 7PD 4PDT (4 Form C) 1A 8.3mA 8.4ma 8.3ma 8.	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 1A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 7ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form 4PDT (4 Form C)  Contact Rating (Current) 1A  Switching Voltage 250VAC, 220VDC - Max  Turn On Voltage (Max) 16.8 VDC  Turn Off Voltage (Min) 2.4 VDC  Operate Time 7ms  Release Time 5ms  Features - Mounting Type Through Hole  Termination Style PC Pin	Coil Current	8.3mA
Contact Rating (Current)  Switching Voltage  250VAC, 220VDC - Max  Turn On Voltage (Max)  16.8 VDC  Turn Off Voltage (Min)  2.4 VDC  Operate Time  7ms  Release Time  5ms  Features  - Mounting Type  Through Hole  Termination Style	Coil Voltage	24VDC
Switching Voltage 250VAC, 220VDC - Max  Turn On Voltage (Max) 16.8 VDC  Turn Off Voltage (Min) 2.4 VDC  Operate Time 7ms  Release Time 5ms  Features -  Mounting Type Through Hole  Termination Style PC Pin	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max)  16.8 VDC  Turn Off Voltage (Min)  2.4 VDC  Operate Time  7ms  Release Time  5ms  Features  - Mounting Type  Through Hole  Termination Style  16.8 VDC  7ms  7ms  7ms  PC Pin	Contact Rating (Current)	1A
Turn Off Voltage (Min)  Operate Time  Release Time  5ms  Features  - Mounting Type  Through Hole  Termination Style  2.4 VDC  7ms  7ms  5ms  Features  - PC Pin	Switching Voltage	250VAC, 220VDC - Max
Operate Time 7ms  Release Time 5ms  Features -  Mounting Type Through Hole  Termination Style PC Pin	Turn On Voltage (Max)	16.8 VDC
Release Time 5ms  Features - Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	2.4 VDC
Features - Mounting Type Through Hole Termination Style PC Pin	Operate Time	7ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	-
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

### G6A-434P-ST20-US-DC24 Guarantees



### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## G6A-434P-ST20-US-DC24 Payment Methods



















## G6A-434P-ST20-US-DC24 Shipping Methods













If you have any question about G6A-434P-ST20-US-DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com