

G6AK-234P-ST-US-DC48 Information

nelsener.com	 G6AK-234P-ST-US-DC48 Omron Electronics Inc-EMC Div Relays Signal Relays, Up to 2 Amps RELAY GEN PURPOSE DPDT 1A 48V - For the pricing/inventory/lead time, please contact us	
For Reference Only	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



G6AK-234P-ST-US-DC48 Specifications

Manufacturer Part Number G6AK-234P-ST-US-DC48 Manufacturer Omron Electronics Inc-EMC Div Category Relays Category Relays Package - Series G6A Relay Type General Purpose Coil Gurrent 4.2mA Coil Current 4.2mA Cointact Form DPDT (2 Form C) Contact Rating (Current) JAC Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.6 VDC Turn Off Voltage (Min) - Querta Time Sms Release Time Sms Features - Furuing Type Prineument		
CategoryRelaysPackage-Package-SeriesG6ARelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current4.2mACoil CurrentMattorContact FormDPDT (2 Form C)Contact Rating (Current)JASwitching Voltage250VAC, 220VDC - MaxTurn ON Voltage (Max)3.6 VDCCurrentSinsRelease TimeSmsRelease Time-Fatures-Mounting TypeFinogh HoleTermination StylePC Pin	Manufacturer Part Number	G6AK-234P-ST-US-DC48
Signal Relays, Up to 2 AmpsPackage-SeriesG6ARelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current4.2mAColl Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage (Max)33.6 VDCTurn On Voltage (Max)-Operate Time5msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG6ARelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current4.2mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.6 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time-Features-Mounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesG6ARelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current4.2mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)-Operate Time5msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Qurrent4.2mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)IASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.6 VDCTurn Off Voltage (Min)-Operate TimeSmsRelease TimeSmsFeatures-Mounting TypePC Pin	Package	-
Coil TypeLatching, Dual CoilCoil Current4.2mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time-Features-Mounting TypeChing HoleTermination StylePC Pin	Series	G6A
Coil Current4.2mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Relay Type	General Purpose
Coil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)-Operate TimeSmsRelease TimeSmsFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Coil Type	Latching, Dual Coil
Contact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Coil Current	4.2mA
Contact Rating (Current)IASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Coil Voltage	48VDC
Switching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)33.6 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Contact Rating (Current)	1A
Turn Off Voltage (Min)-Operate Time5msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Switching Voltage	250VAC, 220VDC - Max
Operate Time5msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	33.6 VDC
Release Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Turn Off Voltage (Min)	-
Features-Mounting TypeThrough HoleTermination StylePC Pin	Operate Time	5ms
Mounting TypeThrough HoleTermination StylePC Pin	Release Time	5ms
Termination Style PC Pin	Features	-
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

G6AK-234P-ST-US-DC48 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.





If you have any question about G6AK-234P-ST-US-DC48, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com